


Product Data Sheet

7600-2300 3X500' - Fabric Only- RWB

7600-2350 3'x1500' RWB Silt Fence Fabric Only

Silt Fence

RWB Striped Silt Fence

Earth Savers DOT grade silt fence is a superior quality woven silt fence designed to meet most DOT and federal standards. This black fabric has a Red, White and Blue deliniation stripe.

Typical Properties	Test Method	Typical Values	
		English	Metric
Material		Polypropylene	
Grab Tensile	ASTM D-4632	135 lbs	61.2 Kg
Grab Elongation	ASTM D-4632	18%	
Mullen Burst	ASTM D-3786	294 PSI	2027 kPa
Puncture	ASTM D-4888	85 lbs	38.5 Kg
Trapezoid Tear	ASTM D-4533	70 lbs	31.8 Kg
Apparent Opening Size	ASTM D-4751	30 Sieve (.023")	.58 mm
Flow Rate	ASTM D-4491	15.5 Gal/Min/ft ²	631.6 L/Min/m ²
Permitivity	ASTM D-4491	0.2 Sec	
Ultraviolet Exposure	ASTM D-4355	80% after 500 Hours	

- Silt fence is a temporary sediment barrier designed to pond sediment-laden water and allow the sediment to fall out of suspension.



Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com

PO Box 2083 Woodland CA, 95776 • Toll Free (866) WATTLES • Fax (530) 668-5140