



GATOR SHAMPOO

FOR CONCRETE PAVERS & NATURAL STONES

TDS Revision Date (dd/mm/yyyy): 01/04/2014



Technical Data Sheet

UPDATE: April 01, 2014

Make sure you have an updated data sheet on hand. Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

<u>DESCRIPTION</u>: GATOR CLEAN SHAMPOO removes ground in dirt from the surface of concrete pavers and natural

stones. It will make the pavers, patio slabs, walls & natural stones look clean and vibrant. Applying GATOR CLEAN SHAMPOO before a sealer application will assure you of a deeper penetration into the

cleaned surface.

FEATURES: • Removes penetrated dirt

• Restores the pavers to it's natural color

• No muriatic acid in product

• Washes off with water

• Will not affect grass, flowers or plantation.

<u>FOR USE ON:</u> for concrete pavers, patios, slabs, walls & natural stones.

COVERAGE: •1 U.S. gal. (3.78 L.) diluted with 4 U.S. gal. (15.1 L.) of water cleans approx. 375 sq. ft (35 sq. m.)

or 75 sq. ft (7 sq. m.) per U.S. gallon (3.78 L.).

•5 U.S. gal. (18.9 L.) diluted with 20 U.S. gal. (75.7 L.) of water cleans approx. 1900 sq. ft (175 sq. m.)

or 75 sq. ft (7 sq. m.) per U.S. gallon (3.78 L.).

<u>PLEASE NOTE:</u> 1. This product is not an efflorescence cleaner.

2. Do not let product dry up on surface.

3. Wear goggles and rubber gloves.

4. Wait at least 60 days after new pavers or stones are installed before using this product.

5. Introduce liquid in 4 parts water, 1 part **GATOR CLEAN SHAMPOO** concentrated liquid and mix, any concentration greater than this can discolor the pavers.

6. Do not apply under hot sun.

7. Keep paver surface wet from start to finish.

IDEAL MIXTURE: 4 parts water – 1 part product

<u>APPLICATION INSTRUCTIONS:</u>

1. Wet paver surface with water.

- 2. Dip a hard bristle brush in a pail containing the mixed product, or with the help of a sprayer, apply the Shampoo on the paver surface and scrub. 1 U.S. gal. (3.78 L.) of diluted product is to be used for every 75 sq. ft. (7 sq.m.) of paver surface.
- 3. Rinse thoroughly with water and move on to the next section of 75 sq. ft. (7 sq.m.).
- 4. Repeat steps 2 & 3 over all the sections in question if needed.
- 5. Once the surface is clean, use a water hose and generously rinse off **GATOR CLEAN SHAMPOO** until there is no more foaming action on the pavers.

NOTE

Repeat steps if there is a lot of dirt trapped in the pavers and natural stones.







GATOR SHAMPOO

FOR CONCRETE PAVERS & NATURAL STONES

TDS Revision Date (dd/mm/yyyy): 01/04/2014



PACKAGING:	Product	Size	per Box	per Pallet	
	Gator Shampoo Cleaner	3.78 L (1 U.S. gal.)	4 units	24 boxes	
	Gator Shampoo Cleaner	18.9 L (5 U.S. gal.)		48 pails	

LIMITED WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose.

DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS.

CAUSES BURNS. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Wear a mask, impervious gloves and safety glasses. Use only in a well-ventilated area. Handle with care.

FIRST AID TREATMENT:

Contains Phosphoric acid, Nitric acid and alcohols, C12-16 ethoxylated. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.









^{*}Please store container at above 32°F / 0°C.

^{*}Pavers and stones should only be sealed 60 days after the installation date.