



## GATOR ROCK BOND - LIQUID BINDING AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 01/04/2014



## Technical Data Sheet

### UPDATE:

April 1, 2014

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

### DESCRIPTION:

Mixed **GATOR ROCK BOND** with 100% washed and dried riverstone, creates a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.

### IDEAL FOR:

- Banding, edging and trimming.
- Pathways.
- Walkways.
- Tree wells.

### FEATURES:

- Porous & permeable.
- Keeps stones in place.
- Reduce maintenance & clean up.
- Durable in extreme conditions.
- Solvent-free.
- High elongation.
- Shock absorption.
- Easy to apply and easy to repair.
- Superb U.V. and weathering resistance.

### INSTALLATION INSTRUCTIONS:


#### TYPES OF ROCK THAT CAN BE USED WITH **GATOR ROCK BOND**:

GRANITE - LIMESTONE - MARBLE (1/8" to 3/8")

these rocks have to be clean, free of dust & 100% dry.

#### **METHOD** of application of **GATOR ROCK BOND**:

1. Prepare a solid base by densely compacting 4" (10 cm) of crushed stones.
2. Mix in a ratio of one container (1 US gal.) of **GATOR ROCK BOND** with (320 lbs) of the above mentioned stones for 4 minutes.  
Mix products automatically with a masonry mixer or you can manually mix on a sheet of plywood or in a wheel barrow.
3. Trowel the mixed riverstone on the surface desired, within 20 minutes after mixing.



### PLEASE NOTE:

- For pedestrian use only.
- Works above 60°F (16°C).
- Allow 24 hours to dry without rain.

### COVERAGE:

1 US gal mixed with 320 lbs of dry stone will cover 80 sq. ft. (7.4 sq. m.). The size of the stone are to be between 1/8" & 3/8" for a minimum 1/2" surface thickness.

### STORAGE:

Store in a cool, dry, well ventilated area. Store in upright position. Store at above freezing temperature 32°F (0°C). Shelf life is 1 year in original unopened container.

### WARNING!

Refer to material safety data sheet for further information. Toxic if swallowed. Avoid ingestion or eye contact. Avoid contact with strong alkalines or acids.



## GATOR ROCK BOND - LIQUID BINDING AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 01/04/2014



### FIRST AID:

#### INGESTION:

Call physician or Poison Control Centre immediately. Do not induce vomiting unless directed to do so by medical personnel. **Eye Contact:** Flush contaminated area with water for 15 minutes. Consult a physician if necessary.

### PACKAGING:

Product	Size	per Box	per Pallet
Gator Rock Bond- Liquid Binding Agent	3.78 L (1 U.S. gal.)	4 units	24 boxes

### WARRANTY:

**ALLIANCE DESIGNER PRODUCTS INC.** cannot guarantee results as it has no control over surface and sub-surface preparation and product application. **ALLIANCE DESIGNER PRODUCTS INC.** agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then **ALLIANCE DESIGNER PRODUCTS INC.** agrees to refund the purchase price. Proof of purchase is required for any claim. **EXCLUSION OF RESPONSIBILITY** THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF **ALLIANCE DESIGNER PRODUCTS INC.** IN ALL EVENTS, **ALLIANCE DESIGNER PRODUCTS INC.**, SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, **ALLIANCE DESIGNER PRODUCTS INC.**, EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.



*Quality is our Strength*