

Max Air

New High Performance motor runs cooler and quieter. Noise levels as low as 65 decibels. Small and compact, ideal for bathtubs: 9" | x 6.5" w x 6.75" h. 1.5" tapered fitting on outlet. Available options include: air or electronic 3- speed control, and heater. The revolutionary new motor dramatically improves performance while running cooler and quieter. Unique housing design with bottom air inlet creates a tortuous path, trapping noise inside the blower for ultra quiet performance. Small profile with easy access mounting tabs makes installation a snap. Certified through Underwriters Laboratory, Canadian Standards, and TUV Rheinland.



Air enters through the bottom of the Max Air blower creating a tortuous path, trapping noise inside the blower

| HP | AMPS | Voltage | Air-Flow (CFM) | Sealed Pressure Inches of H20 |
|-----|------|-----------|-------------------|----------------------------------|
| 1.0 | 4.5 | 110/120 | 105 | 65 |
| 1.0 | 2.5 | 220 / 240 | 105 | 70 |
| 1.5 | 7.4 | 110/120 | 112 | 95 |
| 1.5 | 3.2 | 220 / 240 | 112 | 95 |
| 2.0 | 10.0 | 110/120 | 115 | 125 |
| 2.0 | 5.5 | 220 / 240 | 115 | 120 |

*Inches of water