



# Butterfly Valves - Ductile Iron



HBV Series



HBV GEAR Series



## Ductile Iron Butterfly Valve Features:

- Designed for swimming pool, irrigation and water systems.
- Wafer body features 4 alignment holes.
- Lever lock handle (spring loaded) provides excellent manual control for balancing or shut off services.
- Notched throttling plate allows balancing in 10° increments in any position desired within 90° arc rotation of the disc.
- Positive bubble-tight shutoff with minimum torque.
- Seat face eliminates need for flange gaskets.
- Phenolic backed seats prevent collapse, are stretch resistant, blowout proof and field replaceable.
- **EPDM seats** temperature rated at -30 °F to 275 °F.
- 420 stainless steel shaft
- Bidirectional dead-end capability for 250 psi (2" - 12").
- Compatible with ANSI 125/150 flanges.
- Designed to comply with MSS SP-67 and API 609.
- **Ductile iron, ENP plated disc.**
- Imported

Part No.	Size	Weight(lbs)	Ctn Qty	List Price
<b>Ductile Iron ENP Plated Disc*</b>				
HBV2	2"	7	1	\$ 101.94
HBV21/2	2-1/2"	8	1	119.68
HBV3	3"	10	1	128.54
HBV4	4"	12	1	190.60
HBV5	5"	15.5	1	234.91
HBV6	6"	17.5	1	283.67
HBV8	8"	33	1	452.11
HBV10	10"	50	1	485.53
HBV12	12"	74	1	732.14
<b>Ductile Iron ENP Plated Disc - GEAR DRIVE *</b>				
HBV6-GEAR	6"	28.5	1	393.01
HBV8 GEAR	8"	54	1	632.95

Flanges & Bolt kits available, see page 3.26