



Butterfly Valves - Ductile Iron



HBFV Series

Ductile Iron Butterfly Valve Features:

- Designed for swimming pool, irrigation and water systems.
- Wafer body features 4 alignment holes.
- Lever lock handle (spring loaded) provides excellent manual control for balancing or shut off services.
- Notched throttling plate allows balancing in 10° increments in any position desired within 90° arc rotation of the disc.
- Positive bubble-tight shutoff with minimum torque.
- Seat face eliminates need for flange gaskets.
- Phenolic backed seats prevent collapse, are stretch resistant, blowout proof and field replaceable.
- **EPDM seats** temperature rated at -30° F to 275° F.
- 420 stainless steel shaft
- Bidirectional dead-end capability for 250 psi (2" - 12").
- Compatible with ANSI 125/150 flanges.
- Designed to comply with MSS SP-67 and API 609.
- **Ductile iron, ENP plated disc.**
- Imported



HBFV GEAR Series



| Part No. | Size | Weight(lbs) | Ctn Qty | List Price |
|--|--------|-------------|---------|-----------------|
| Ductile Iron ENP Plated Disc* | | | | |
| HBFV2 | 2" | 7 | 1 | \$ 81.58 |
| HBFV2 1/2 | 2-1/2" | 8 | 1 | 95.77 |
| HBFV3 | 3" | 10 | 1 | 102.86 |
| HBFV4 | 4" | 12 | 1 | 152.53 |
| HBFV5 | 5" | 15.5 | 1 | 187.99 |
| HBFV6 | 6" | 17.5 | 1 | 227.01 |
| HBFV8 | 8" | 33 | 1 | 361.80 |
| HBFV10 | 10" | 50 | 1 | 535.61 |
| HBFV12 | 12" | 74 | 1 | 585.90 |
| Ductile Iron ENP Plated Disc - GEAR DRIVE * | | | | |
| HBFV6-GEAR | 6" | 28.5 | 1 | 314.51 |
| HBFV8 GEAR | 8" | 54 | 1 | 506.52 |
| Replacement Handles for HBFV Series | | | | |
| BFH2 | 2" | | 1 | 17.46 |
| BFH3 | 3" | | 1 | 17.46 |
| BFH4 | 4" | | 1 | 17.46 |
| BFH5 | 5" | | 1 | 20.87 |
| BFH6 | 6" | | 1 | 20.87 |
| BFH8 | 8" | | 1 | 42.94 |
| BFH10 | 10" | | 1 | 42.94 |
| BFH12 | 12" | | 1 | 48.88 |

Flanges & Bolt kits available, see page 3.26