



# Clear Braided PVC Hose



## Clear Braided PVC Hose

### Standard Wall, Class 125 Features:



- Flexible, see through clear hose with braid pattern reinforcement of two polyester spirals.
- Flexible clear PVC NSF 51 certified to 100°F (38°C), USP CLASS V1 rated.
- All hose compound ingredients used are listed in US FDA CFR, Title 21.
- Temperature range + 25° to 150° F / -5° to +65°C.
- Silicone free.
- Food and beverage grade, standard wall.
- Use for air, water lines.

| Part Number | Nominal (inches) |       | Max Working Pressure |           | Reel Length | Approx Wt per CFT. | List Price Per Reel |
|-------------|------------------|-------|----------------------|-----------|-------------|--------------------|---------------------|
|             | ID               | OD    | PSI@68°F             | PSI@122°F |             |                    |                     |
| CBH25-1     | 1/4              | 0.438 | 250                  | 105       | 100'        | 5.7 lbs            | \$ 127.68           |
| CBH38-1     | 3/8              | 0.594 | 225                  | 97        | 100'        | 9.0 lbs            | 177.94              |
| CBH50-1     | 1/2              | 0.750 | 200                  | 86        | 100'        | 13.8 lbs           | 244.32              |
| CBH58-1     | 5/8              | 0.875 | 200                  | 86        | 100'        | 16.5 lbs           | 290.94              |
| CBH75-1     | 3/4              | 1.030 | 150                  | 65        | 100'        | 21.9 lbs           | 366.43              |
| CBH100-1    | 1                | 1.300 | 125                  | 54        | 100'        | 31.5 lbs           | 454.88              |
| CBH100-2    | 1                | 1.300 | 125                  | 54        | 200'        | 31.5 lbs           | 850.25              |
| CBH125-50   | 1 1/4            | 1.625 | 100                  | 43        | 50'         | 45.0 lbs           | 447.99              |
| CBH125-1    | 1 1/4            | 1.625 | 100                  | 43        | 100'        | 45.0 lbs           | 896.01              |
| CBH150-50   | 1 1/2            | 1.937 | 100                  | 43        | 50'         | 64.0 lbs           | 570.01              |
| CBH150-1    | 1 1/2            | 1.937 | 100                  | 43        | 100'        | 64.0 lbs           | 1139.98             |
| CBH200-1    | 2                | 2.490 | 75                   | 33        | 100'        | 95.0 lbs           | 1829.08             |

**\*\* Temperatures higher than 68° F reduce available working pressure. See next page for temperature, working pressure calculation chart and cautionary note.**