8" ROUND MOFLOW® SUCTION OUTLET COVER AND MUD FRAME



Certified to NSF/ANSI/CAN 50 ANSI/APSP/ICC-16 2017 Open Area 16.6 in² For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode



FEATURES

Certified, Listed, and Labeled in conformance with APSP/ANSI/ICC-16 2017 and NSF/ANSI/CAN 50 standards

Manufactured from superior UV-resistant engineered polymers

#316 stainless steel screws

Online product support including downloadable CAD files, General Certificate of Conformity, third-party certificate, installation instructions and more

Replace drain cover every five years from the date of installation

See next page for additional product configurations

36 per case




Part # 8MFxxx


Designed to replace standard 8" round covers that have a 7" center-to-center screw hole measurement


STANDARD COLORS

- 8MF101 White
- 8MF102 Black
 - 8MF103 Light Gray
- 8MF104 Blue
- 8MF105 Dark Gray
 - 8MF108 Tan

Also available as frame only p/n 8FRxxx 24 per case







- 1. 8" Round Mud Frame
- 2. 8" Round MoFlow Suction Outlet Cover
- 3. 10 x 3/4" Flat Head Phillips, 316 SS, Qty 4 $\,$

Standard 2" NPT, 2" Socket Extended ABS Sump

VGBA CERTIFIED SPECIFICATIONS

For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode



6" Socket Deep PVC Sump

VGBA CERTIFIED SPECIFICATIONS


For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode





Part # 8MFSBACxxx 8 per case


Part # 8MFSBAC2xxx Contractor's 2-Pack 4 per case



- 1. 2" Socket x 1-1/2" Socket Pipe Reducer
- 2. Standard ABS Sump
- 3. 2" Tapered Threaded Pipe Plug
- 4. 8" Sump Bucket Collar
- 5. 8" MoFlow Suction Outlet Cover
- 6. 10 x 3/4" Flat Head Phillips, 316 SS, Qty 4







- 1. 6" Socket Deep PVC Sump 2. 6" Tapered Threaded Pipe Plug
- 3. 8" MoFlow Suction Outlet Cover 4. 10 x 3/4" Flat Head Phillips, 316 SS, Qty 4

3" Socket x 4" Spigot Side Port PVC Sump



Certified to NSF/ANSI/CAN 50 ANSI/APSP/ICC-16 2017 **Open Area** 16.6 in²

For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode



Part #

8MFxxxSSB

4 per case

Hassle-free pressure testing and winterizing







testing and winterizing Comes with a 3" and 2" NPT cap with O-ring.

No knock-outs required. 2" Plug and O-Ring, p/n 2SBP101 3" Plug and O-Ring, p/n 3SBP101



Ontional 2" hydrostatic relief valve available







- 1. Side Port Sump Bucket, 8" Round Frame 2. 2" NPT Plug O-Ring
- 3. 2" NPT Plug
- 4. 3" NPT Plug O-Ring
- 5. 3" NPT Plug
- 6. 8" Round MoFlow Suction Outlet Cover
- 7. 10 x 3/4" Flat Head Phillips, 316 SS, Qty 4