

**SAFETY DATA SHEET**

according to US Regulation 29 CFR 1910.1200 and the Canadian HPA

**DRYTEC GRANULAR  
Level (MUL) for potable water is 15 mg/L****Maximum Use**

Version 2.2

Revision Date 2020.07.27

Print Date 2021.07.21

**SECTION 1. IDENTIFICATION**

Product name : DRYTEC GRANULAR  
Maximum Use Level (MUL) for potable water is 15 mg/L

**Manufacturer or supplier's details**

Company : Innovative Water Care, LLC  
1400 Bluegrass Lakes Parkway  
Alpharetta, GA  
30004

Telephone : 1-800-511-6737 (Outside the USA: 1-423-780-2347)  
E-mail address : sds@sigurawater.com  
Emergency telephone number : 1-800-654-6911 (Outside the USA: 1-423-780-2970)

**Recommended use of the chemical and restrictions on use**

Recommended use : Water treatment chemical

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Oxidizing solids : Category 2  
Acute toxicity (Oral) : Category 4  
Acute toxicity (Inhalation) : Category 3  
Skin corrosion : Category 1B  
Serious eye damage : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

**GHS label elements**

Hazard pictograms :



**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use**

Signal word	: Danger
Hazard statements	: H272 May intensify fire; oxidizer. H302 Harmful if swallowed. H331 Toxic if inhaled. H314 Causes severe skin burns and eye damage. H335 May cause respiratory irritation.
Precautionary statements	: <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P220 Keep/ Store away from clothing/ combustible materials. P221 Take any precaution to avoid mixing with combustibles. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P301 + P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor. P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use water spray to extinguish. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/container in accordance with local regulation.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Mixture

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use****Hazardous components**

Chemical name / Synonyms	CAS-No.	Concentration (% w/w)
Calcium hypochlorite	7778-54-3	65 - 75
Calcium chlorate	10137-74-3	0 - 5
Calcium chloride	10043-52-4	0 - 5
Calcium dihydroxide	1305-62-0	0 - 4

**SECTION 4. FIRST AID MEASURES**

- General advice : Call a poison control center or doctor for treatment advice. For 24-hour emergency medical assistance, call Arch Chemical Emergency Action Network at 1-800-654-6911. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.
- If inhaled : IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
- In case of skin contact : IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
- In case of eye contact : IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
- If swallowed : IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Probable mucosal damage may contraindicate the use of gastric lavage.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Water only.  
Do not use dry extinguishers containing ammonium com-

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use**

- pounds.
- Specific hazards during firefighting : Strong oxidizing agent
- Further information : Use water to cool containers exposed to fire. See Section 6 for protective equipment for fire fighting.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Response to a large quantity spill (100 pounds or greater) or when dusting or decomposition gas exposure could occur requires the use of a positive pressure full face supplied air respirator or self contained breathing apparatus (SCBA), chemical resistant gloves, coveralls and boots. In case of fire, this personal protective equipment should be used in addition to normal fire fighter equipment.  
Hazardous concentrations in air may be found in local spill area and immediately downwind.  
Remove all sources of ignition.  
Stop source of spill as soon as possible and notify appropriate personnel.  
Contact 1-800-654-6911 immediately. DANGER: All spills of this product should be treated as contaminated. Contaminated product may initiate a chemical reaction that may spontaneously ignite any combustible material present, resulting in a fire of great intensity. In case of a spill, separate all spilled product from packaging, debris and other material. Using a clean broom or shovel, place all spilled product into plastic bags, and place those bags into a clean, dry disposal container, properly marked and labeled. Disposal containers made of plastic or metal are recommended. Do not seal disposal containers tightly. Immediately remove all product in disposal containers to an isolated area outdoors. Place all damaged packaging material in a disposal container of water to assure decontamination (i.e. removal of all product) before disposal. Place all undamaged packaging in a clean, dry container properly marked and labeled. Call for disposal procedures. For disposal considerations see section 13.
- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal. Do not flush into surface water or sanitary sewer system. Avoid dust formation.

**SECTION 7. HANDLING AND STORAGE**

## DRYTEC GRANULAR Level (MUL) for potable water is 15 mg/L

## Maximum Use

- |  |   |
|--|---|
| Advice on safe handling                  | : Avoid inhalation of dust and fumes.<br>Do not take internally. Avoid contact with skin, eyes and clothing. Upon contact with skin or eyes, wash off with water.<br>Remove contaminated clothing and wash before reuse.  |
| Conditions for safe storage              | : Keep product tightly sealed in original containers. Store product in a cool, dry, well-ventilated area. Store away from combustible or flammable products. Keep product packaging clean and free of all contamination, including, e.g. other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc. |
| Materials to avoid                       | : Do not allow product to come in contact with other materials, including e.g. other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc. A chemical reaction with such substances can cause a fire of great intensity.   |
| Further information on storage stability | : Average daily temperature of 35° C / 95° F. Storage above this temperature may result in rapid decomposition, evolution of chlorine gas and heat sufficient to ignite combustible products.   |

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium dihydroxide	1305-62-0	TWA	5 mg/m <sup>3</sup>	ACGIH
		REL	5 mg/m <sup>3</sup>	NIOSH/GUIDE
		PEL (Total dust.)	15 mg/m <sup>3</sup>	OSHA_TRANS
		PEL (Respirable fraction.)	5 mg/m <sup>3</sup>	OSHA_TRANS
		TWA	5 mg/m <sup>3</sup>	Z1A

- Engineering measures** : Local exhaust ventilation or other engineering controls are normally required when handling or using this product to keep airborne exposures below the TLV, PEL or other recommended exposure limit.

## **DRYTEC GRANULAR** **Level (MUL) for potable water is 15 mg/L**

## **Maximum Use**

### **Personal protective equipment**

Respiratory protection : Wear a NIOSH approved respirator if levels above the exposure limits are possible.  
A NIOSH approved full-face air purifying respirator equipped with combination chlorine/P100 cartridges. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres or if exposure concentrations exceed ten (10) times the published limit.

Hand protection

Remarks : Wear impervious gloves to avoid skin contact. A full impervious suit is recommended if exposure is possible to a large portion of the body.

Eye protection : Use chemical goggles.

Skin and body protection : Neoprene, Nitrile, Natural rubber (This includes: gloves, boots, apron, protective suit)

Protective measures : An eye wash and safety shower should be provided in the immediate work area.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : free flowing, granular

Colour : off-white

Odour : Chlorine-like

Odour Threshold : no data available

pH : 10.5 - 11.5 (77 °F / 25 °C)  
Concentration: 1 %

Melting point/freezing point : Not applicable

Boiling point/boiling range : no data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : This product is chemically reactive with many substances. Any contamination of the product with other substances by spill or otherwise may result in a chemical reaction and fire.

Flammability (liquids) : no data available

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use**

---

Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: no data available
Relative density	: Not applicable
Density	: 0.8 g/cm <sup>3</sup>
Water solubility	: ca. 180 g/l (77 °F / 25 °C)
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Decomposition temperature	: no data available
Viscosity, dynamic	: no data available
Viscosity, kinematic	: no data available
Oxidizing properties	: Oxidizing

---

**SECTION 10. STABILITY AND REACTIVITY**

Possibility of hazardous reactions	: NFPA Oxidizer Class: Meets the criteria of an NFPA Class 3 Oxidizer
Conditions to avoid	: Do not store next to heat source, in direct sunlight, or elevated storage temperature. Do not store where the daily average temperature exceeds 95 °F. Prevent ingress of humidity and moisture into container or package. Always close the lid.
Incompatible materials	: This product is chemically reactive with many substances, including, e.g., other pool treatment products, acids, organics, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, corrosive, flammable or combustible materials. Do not allow product to contact any foreign matter, including other water treatment products. Contamination or improper use may cause a fire of great intensity, explosion or the release of toxic gases. If product is exposed to small amounts of water, it can react violently to produce heat and toxic gases and spatter.
Hazardous decomposition products	: Chlorine

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use**

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation, skin, eyes, ingestion

**Acute toxicity**

Acute oral toxicity : LD50 (Rat): approximately 800 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.04 mg/l  
Exposure time: 1 h  
Remarks: (Nose Only)

LC50 (Rat): > 0.51 mg/l  
Exposure time: 4 h  
Remarks: (Nose Only)

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

Remarks: DRY MATERIAL CAUSES MODERATE SKIN IRRITATION.  
WET MATERIAL CAUSES SKIN BURNS.

**Serious eye damage/eye irritation**

Result: Corrosive to eyes

**Respiratory or skin sensitisation**

Remarks: This material is not known or reported to be a skin or respiratory sensitizer.

**Carcinogenicity****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**Further information**

Remarks: no data available



**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L**

**Maximum Use**

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

no data available

### Persistence and degradability

no data available

### Bioaccumulative potential

no data available

### Mobility in soil

no data available

### Other adverse effects

Ozone-Depletion Potential : Regulation: US. EPA Clean Air Act (CAA) Section 602 Ozone-Depleting Substances (40 CFR 82, Subpt. A, App A & B)  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Highly toxic to fish and other aquatic organisms.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : If this product becomes a waste, it meets the criteria of a hazardous waste as defined under 40 CFR 261 and would have the following EPA hazardous waste number: D001.  
As a hazardous solid waste, it must be disposed of in accordance with local, state and federal regulations.

---

## SECTION 14. TRANSPORT INFORMATION

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use****DOT**

**UN number** : 2880  
**Proper shipping name** : Calcium hypochlorite, hydrated mixtures  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Labels** : 5.1  
**Emergency Response Guidebook Number** : 140  
**Environmental hazards** : yes

**TDG**

**UN number** : 2880  
**Proper shipping name** : CALCIUM HYPOCHLORITE, HYDRATED MIXTURE  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Labels** : 5.1  
**Environmental hazards** : yes

**IATA**

**UN number** : 2880  
**Proper shipping name** : Calcium hypochlorite, hydrated mixture  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Labels** : 5.1  
**Environmental hazards** : yes

**IMDG**

**UN number** : 2880  
**Proper shipping name** : Calcium hypochlorite, hydrated mixture  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Labels** : 5.1  
**EmS Number 1** : F-H  
**EmS Number 2** : S-Q  
**Environmental hazards** : Marine pollutant: yes

**ADR**

**UN number** : 2880  
**Proper shipping name** : CALCIUM HYPOCHLORITE, HYDRATED MIXTURE  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Classification Code** : O2  
**Hazard Identification Number** : 50  
**Labels** : 5.1  
**Environmental hazards** : yes

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use****RID**

**UN number** : 2880  
**Proper shipping name** : CALCIUM HYPOCHLORITE, HYDRATED MIXTURE  
**Transport hazard class** : 5.1  
**Packing group** : II  
**Classification Code** : O2  
**Hazard Identification Number** : 50  
**Labels** : 5.1  
**Environmental hazards** : yes

**Special precautions for user** : none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not applicable

**SECTION 15. REGULATORY INFORMATION**

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals.

**EPA Registration number** : 1258-427  
**Signal word** : DANGER!  
**Hazard statements** : Highly Corrosive.  
Causes skin and eye damage.  
May be fatal if swallowed.  
Irritating to nose and throat.  
This pesticide is toxic to fish and aquatic organisms.

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Calcium hypochlorite	7778-54-3	10	13

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards**

See above: SECTION 2. Hazard Identification-GHS Classification



## DRYTEC GRANULAR Level (MUL) for potable water is 15 mg/L

## Maximum Use

### SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

### Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Components	CAS-No.	Component RQ (lbs)
Calcium hypochlorite	7778-54-3	10

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Components	CAS-No.	Concentration
Calcium hypochlorite	7778-54-3	65 - 75 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

## US State Regulations

### Massachusetts Right To Know

Components	CAS-No.
Calcium hypochlorite	7778-54-3
Calcium chlorate	10137-74-3
Calcium carbonate	471-34-1
Calcium dihydroxide	1305-62-0

### Pennsylvania Right To Know

Components	CAS-No.
Calcium hypochlorite	7778-54-3



**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L**

**Maximum Use**

Sodium chloride	7647-14-5
Calcium chloride	10043-52-4
Calcium chlorate	10137-74-3
Calcium carbonate	471-34-1
Calcium dihydroxide	1305-62-0

**New Jersey Right To Know**

Components	CAS-No.
Calcium hypochlorite	7778-54-3
Sodium chloride	7647-14-5
Calcium chloride	10043-52-4
Calcium chlorate	10137-74-3
Calcium carbonate	471-34-1
Calcium dihydroxide	1305-62-0

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**Canadian lists**

**NPRI**

Canadian National Pollutant Release Inventory (NPRI): No component is listed on NPRI.

**The components of this product are reported in the following inventories:**

TSCA : This is an EPA registered pesticide.

**SECTION 16. OTHER INFORMATION**

**Full text of other abbreviations**

ACGIH : US. ACGIH Threshold Limit Values  
NIOSH/GUIDE : US. NIOSH: Pocket Guide to Chemical Hazards, as amended  
OSHA\_TRANS : US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)  
Z1A : US. OSHA Table Z-1-A (29 CFR 1910.1000)

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response

**DRYTEC GRANULAR**  
**Level (MUL) for potable water is 15 mg/L****Maximum Use**

Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

1

Revision Date : 2020.07.27

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Date format : yyyy/mm/dd

US / EN