

DIRECTIONS FOR USE

Preparation Existing Concrete: All paint, oil, and grease must be removed from the surface either mechanically or chemically using Uni-Stripp. Clean surface with GREASE-A-WAY per directions. After cleansing, rinse or pressure wash surface completely and allow to dry.

Stamped Concrete: Surface must be free of all un-bonded release agent powder or liquid release prior to application of sealer.

Application: Apply at a uniform coverage rate with an industrial hand-held pump-up sprayer equipped with a 0.5 gal/min (1.9 L/min) tip and neoprene fittings. Common garden-type sprayers should not be used. CRYSTAL CLEAR VOC dries quickly. While spraying, keep the sprayer tip within 8 in (20 cm) of the concrete surface. Back-roll over spray-applied sections using a short, 1/4 in (0.65 cm) nap, solvent-resistant roller cover. It is helpful to keep the roller wet with CRYSTAL CLEAR VOC or SOLV-KLEEN while rolling. If applying CRYSTAL CLEAR VOC by roller only, use a 1/4 in (0.64 cm) nap, solvent-resistant roller cover. Keep the roller wet and keep a wet edge while applying to avoid lap marks. Rolling back and forth excessively will cause bubbling. In all cases, allow the first coat dry tack-free before applying the second coat. Best performance and appearance is achieved with two THIN coats following the coverage recommendations.

To create a non-slip surface, add SHUR GRIP to the final coat of sealer. MATTE ADD may be used if a satin or low-gloss finish is preferred.

CLEAN-UP

Use SOLV-KLEEN, xylene, or acetone for cleaning tools.

PRECAUTIONS/LIMITATIONS

- CRYSTAL CLEAR VOC liquid and vapors are highly flammable. Keep away from heat/sparks/open flames/hot surfaces.
- Avoid breathing fume/gas/mist/vapors/spray. Use only in well-ventilated areas.
- Heavy applications, too many successive coats, or multiple coats over time may cause bubbling, whitening, peeling and ultimate failure of the product.
- Do not apply when concrete surfaces or ambient temperatures are below 40 °F (4 °C). Do not apply in hot, direct sun or when the temperature is above 85 °F (29 °C).
- Do not apply if rain is expected within 12 hours of application.
- Not resistant to gasoline or other automotive fluids. May show tire marks and stains.
- Do not thin this product.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 08.15

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.