# BOSS<sub>®</sub> PRODUCTS



# **635C Contact Adhesive**

## PROFESSIONAL GRADE

Part Number: 63510



- Domed can
- · One year shelf life
- Non-Chlorinated
- Fast Drying
- High Strength
- Web Spray
- Formulated with high solids
- VOC compliant
- Prop 65 compliant

#### THE IDEAL SEALANT/ADHESIVE FOR:

- Fabric
- Paper
- Plastic
- Corrugated
- Felt
- Wood
- Cork
- Metal
- Foam
- · IVIELA
- roam
- And more...
- Insulation

Visit Our Website for Other **BOSS® MADE TO WORK** Products

www.bossproducts.com

Call The BOSS® 800-928-BOSS

**Soudal Accumetric** 

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412



# BOSS® PRODUCTS



# **635C Contact Adhesive**

### PROFESSIONAL GRADE

#### **TYPICAL PROPERTIES**

BaseSingle Component	t Polyurothano
	-
ConsistencyCollapsible	
Curing SystemMoisture Cure At Room Temperature	
Curing Time (*)	About 4 hours
Skin Formation (*)Abo	out 20 minutes
Full Strength (*)A	bout 24 hours
Post expansion	Minimal
Shear Strength (Wet Lumber) (ASTM D3498)	205 psi
Shear Strength (Dry Lumber) (ASTM D3498)	283 psi
Shear Strength (Frozen Lumber) (ASTM D3498)	587 psi
Moisture Resistance (ASTM D3498)	316 psi
Temperature Resistance	40°F to +194°F
	o max. 1 hour)
UL 723 (ASTM E 84) Fire TestFla	ame spread 15
Smoke	developed 35
Information on this data sheet is subject to change without notice and should not be used for writing specifications.	

#### **LIMITATIONS**

· Not watertight

#### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE, AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

For additional information on specific applications, contact Soudal Accumetric.

## Call The **BOSS**® 800-928-BOSS

### **Soudal Accumetric**

350 Ring Road • Elizabethtown • KY 42701 (270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412 www.bossproducts.com



