

BOSS[®]
PRO**SELF
LEVELING****822****JOINT SEALANT**

EXPANSION POOL DECKING, PATIOS, DRIVEWAYS

BOSS[®] 822

Expansion Joint Sealant is a free flowing, self-leveling, one component material. Its flowable characteristics allow it to fill in joints and cracks to make a smooth and permanent seal. Supplied ready-to-use, this material cures at room temperature to a tough, rubbery solid. It adheres well to most common construction substrates including concrete, wood, vinyl, glass and various plastics. **BOSS[®] 822** Expansion Joint Sealant resists weathering, moisture, vibration, ozone, thermal expansion and temperature extremes. Stays flexible from -85°F to 400°F (-65°C to 204°C).

COLORS:**Cartridge**

142931 - White

142930 - Tan

142929 - Grey

Custom colors available
upon request**FEATURES:**

- One component
- Free flowing
- 50% movement
- Self-leveling
- Good adhesion to a wide variety of substrates
- VOC compliant

THE IDEAL SEALANT/ADHESIVE FOR:

- Concrete
- Brick
- Masonry
- Wood
- Glass
- Vinyl
- Most Plastics

PACKAGING:

- 28 oz. Cartridge
- 4.5 Gallon Pail
- Other sizes available upon request

Scan the QR Code to see the
full line of **BOSS^{PRO}** Products!

Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**SELF
LEVELING****822****JOINT SEALANT**

EXPANSION

POOL DECKING, PATIOS, DRIVEWAYS

TYPICAL PROPERTIES*Uncured*

Chemistry	Oxime
Viscosity (cps)	110,000
Specific Gravity	1.17
Tack-Free Time	30 minutes
Application Temperature	-35°F to 140°F

Cured - Physicals

Hardness, Shore A	23 points
Tensile Strength	150 psi
Elongation	300%
Service Temperature	-40°F to 325°F

TESTS*Adhesion-in-Peel*

Poplar	20
Oak	20
Pine	20
Concrete	15

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

None

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com


Soudal
Soudal Accumetric