

# RGBW LAMPS + CONTROLS

# SMART PRODUCTS



**G4**

RoHS FC

2.5 Watts  
190-250 Lumens  
RGBW



**MR16**

RoHS FC

6 Watts  
328-441 Lumens  
RGBW



**PAR36**

RoHS FC

9 Watts  
442-686 Lumens  
RGBW

TECHNICAL REQUIREMENTS: All Chameleon lamps must have consistent 2.4 GHz Wi-Fi signal at the installation location with dBm strength of -70 or better. See the Brilliance Smart Products Guide for more information and troubleshooting.

## SMART SOCKET 2

- Control all lighting functionality
- Pair with Transformer for astronomical timing
- ETL Listed



## LOW VOLTAGE DIMMER

- Control dimming
- 10 Amp capacity
- No minimum load
- Up to 120 watts



TECHNICAL REQUIREMENTS: Must have consistent 2.4 GHz Wi-Fi signal at the installation location with dBm strength of -70 or better. See the Brilliance Smart Products Guide for more information and troubleshooting. Must be placed in landscape lighting transformer or in a covered receptacle box.

TECHNICAL REQUIREMENTS: Always use the supplied gasket to protect against water ingress. In applications where the environment can be extremely wet, we recommend using a cover to protect against water ingress.



Brilliance | [brillianceled.com](http://brillianceled.com) | 800.867.2108