

# LIGHT BAR



## DESCRIPTION

The Light Bar is easy to install and its rugged construction and black aluminum rail makes it a great fit for high-traffic areas. Light Bars are dimmable with most magnetic transformers and the frosted design offers continuous light. Enhanced ESD (Electro-Static Discharge) protection (IEC-61000-4-2). UL Certified E511083.

Optional light bar shields in Copper or Stainless Steel are available in Small and Medium only.

## LIGHT BAR

Use	<b>Areas with Elevation Changes or Dark Sky Requirements Deck, Step, &amp; Hardscape Applications</b>	
Includes	<b>Integrated Light Bar, LightingShrink Professional Crimp, and Heat Shrink Cable Connector</b>	
Warranty	<b>5 Year Warranty on Light Bars</b>	
Integrated Lamp	<b>Small - 1.5W, 110 Lumens, 5.125" Length, CRI 85, IP65, 8-15VAC, 1.67VA, 5 yr warranty, 30,000 hrs</b>	
	<b>2700K</b>	BRI-LB-LED-2700-S
	<b>3000K</b>	BRI-LB-LED-3000-S
	<b>Amber</b>	BRI-LB-LED-AMBER-S
	<b>Medium - 2.5W, 200 Lumens, 9.0" Length, CRI 85, IP65, 8-15VAC, 2.78VA, 5 yr warranty, 30,000 hrs</b>	
	<b>2700K</b>	BRI-LB-LED-2700-M
	<b>3000K</b>	BRI-LB-LED-3000-M
	<b>Amber</b>	BRI-LB-LED-AMBER-M
	<b>Large - 4W, 300 Lumens, 12.875" Length, CRI 85, IP65, 8-15VAC, 4.40VA, 5 yr warranty, 30,000 hrs</b>	
	<b>2700K</b>	BRI-LB-LED-2700-L
	<b>3000K</b>	BRI-LB-LED-3000-L
Accessories	<b>Mounting Bracket</b>	
	<b>Small</b>	BRI-MB-LED-S
	<b>Medium</b>	BRI-MB-LED-M
	<b>Large</b>	BRI-MB-LED-L
	<b>Light Bar Shield</b>	
	<b>Small Copper</b>	LBS-S-C
	<b>Small Stainless</b>	LBS-S-SS
	<b>Medium Copper</b>	LBS-M-C
	<b>Medium Stainless</b>	LBS-M-SS

NEC® Article 411.5 (B): Lighting systems shall be installed not less than 3m (10ft) horizontally from the nearest edge of the water, unless permitted by Article 680.

