

SPA LIGHT SPECIFICATIONS



The Vivid 360 LED Spa Light is a state-of-the art lighting system designed to be retrofitted into popular existing spa niches via its innovative adjustable locking tab, and is also perfect for new spa construction. The light is compact and stylish, with a distinctive lens design providing for a striking LED color blend and diffused beam.

The all-plastic construction of the light removes the need for bonding or grounding and ensures safety to spa users. Available in fixed colors of white, warm white and blue together with multi-color models that can be operated from popular third-party controllers.

Model		color Temp or Wavelength	Lumens	Power Consumption	Incandescent Equivalent	
ALL LIGHTS OPERATE FROM 12V AC ~ 14V AC POWER SUPPLY UL Listed for installation with the top of the luminaire lens not less than 100mm (4") below the normal water level of the pool.						
VLS4004-WT	Cool White	6500K	985	25VA	165 watts	
VLS4014-WW	Warm White	2850K	900	25VA	155 watts	
VLS4008-BL	Blue	465nm	300	25VA	N/A	
VLS4000-T	Amber (Turtle Friendly)	>560nm	425	13VA	N/A	
VLS4000-P	Multi-Color PENTAIR (held on white)	4,000K	850	25VA (30VA max)	140 watts	
VLS4000-J	Multi-Color JANDY + WALL SWITCH (held on white)	Н 4,000К	650	21VA (30VA max)	110 watts	
VLS4000-H	Multi-Color HAYWARD (held on white)	>10,000K	380	16VA (30VA max)	65 watts	

## MAXIMUM CABLE LENGTHS For VIVID 360 LED Spa Lights

Voltage	18AWG 14AWG	18AWG 14AWG		
	MULTI-COLOR	FIXED COLOR		
12V	60ft 130ft	70ft 150ft		
13V	90ft 190ft	100ft 220ft		
14V	120ft 250ft	140ft 310ft		





Plug Kit factory-fitted on 18AWG Cable



## VIVID PLUG KIT - SPA

An innovative feature of the Vivid 360 LED Spa Light is its connectivity. The unique and patented waterproof Plug Kit is factory fitted to the supply cord, and allows for simple connection and detachment to the rear of the light. For spa remodels, this means that the light can be safely stored away until the renovation is completed—thus protecting it from construction work. Available 18AWG Cord Lengths are 50ft, 100ft & 150ft.