



1 gallon (3.785L)

Z Release™ is a specially formulated colorless bond breaker designed to prevent freshly placed concrete from adhering to texturing mats and form liners.

ZR-004

DIRECTIONS: Place, vibrate and float the concrete surface according to standard ACI recommendations. Cover or protect adjacent surfaces. Following the initial floating, when excess moisture is no longer evident, apply Z Release liberally to the texture mats and to the concrete using a pump type sprayer. To avoid evaporation of the material, apply Z Release only in the area where the next few mats are to be placed. One gallon Z Release will be sufficient for approximately 150 square feet of concrete surface. Immediately begin the texturing application. Do not trowel or mix Z Release into the concrete surface. To make corrections on the plastic concrete surface, use the texturing tool to press out unwanted impressions. Upon completion of the stamping process, clean texturing mats using plain water. If using a form liner, apply Z Release liberally to the liner with pump type sprayer or spray bottle moments before placing concrete. Once concrete is sufficiently set, you can deform and rinse liners with plain water.

WARNINGS: Z Release is a COMBUSTIBLE LIQUID! Wear protective clothing and safety glasses during application. Do not apply Z Release in or around buildings occupied by non-construction personnel, as the solvent odors may be irritating. Wear protective clothing, respirator and safety goggles during handling and placement to avoid contact with skin and eyes. Use with adequate ventilation. Avoid breathing vapors. People with medical conditions, or who are pregnant should not be exposed to vapors or fumes. All HVAC openings, windows and air intakes should be closed during exterior applications as well to prevent intake of fumes into the building interior. Z Release is not to be applied in or near areas containing food products. These should be removed and only returned after all solvent vapors have dissipated. For compliance with AIM Clean Air Act regulations, thinning of this product is not allowed. Make sure that the application is static free. Keep Z Release away from sparks, open flame, and sources of ignition. Store away from heat. Do not take internally. Protect all grass, foliage and related landscaping from contact with Z Release. Use with OSHA/NIOSH approved eye protection and air respirator. Empty container may contain explosive vapors that are heavier than air. Keep container closed. Do not cut or weld on or near empty container. Refer to product M.S.D.S. (Material Safety Data Sheet) for further health and safety information. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. For medical emergencies only, call Chemtrec at 1-800-424-9300.

V.O.C. Content: 445 g/L (3.71 lb./ gallon) per EPA Method 24*

H.M.I.S. CODES: HEALTH = 2, FLAMMABILITY= 2, REACTIVITY = 0, PPROTECTION = G

SHIPPING NAMES: Petroleum Naphtha, Combustible Liquid N.O.S., Hazard Class 2, NA 1993,

Packing Group III

SHIPPING CLASS: ITEM 155250, SUB 2, LTL 65 - Concrete Release Agent

PACKAGING: 1-gallon (3.785 L) jugs.

STORAGE: 40 to 90° F.

SHELF LIFE: 1-2 years properly stored

LIMITED WARRANTY: This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.

For more information visit our website at
www.concretecountertopsolutions.com

Concrete Countertop Solutions
790 Northern Blvd. Suite B, Clarks Summit, PA 18411

