



**NATIONWIDE
CONSTRUCTION +
EROSION SUPPLY**

WWW.CDOWWHOLESALE.COM

WIRE BACKED SILT FENCE SPECIFICATIONS

WIRE SIZE:	16 GAUGE , 24" X 100'
MESH OPENNING	2" X 4"
FABRIC SIZE:	36" X 100'

FABRIC SPECIFICATION

GRAB TENSILE STRENGTH:	144/115LBS (TESTING METHOD:ASTM D4632)
GRAB TENSILE ELONGATION:	49% (TESTING METHOD:ASTM D4632)
MULLEN BURST STRENGTH:	225LBS (TESTING METHOD:ASTM D3786)
PUNCTURE STRENGTH:	75LBS (TESTING METHOD:ASTM D4833)
TRAPEZOIDAL TEAR:	62LBS (TESTING METHOD:ASTM D4533)
APPARENT OPENING:	30 U.S. STD SIEVE (TESTING METHOD:ASTM D4751)
FLOW RATE/PERMITTIVITY:	20 GPM/SQ.FT. (TESTING METHOD:ASTM D4491)
UV RESISTANCE:	90% STRENGTH AFTER 500HOURS (TESTING METHOD:ASTM D4355)
MASS/UNIT:	100 GSM (TESTING METHOD:ASTM D5261)