



Step #	Installation Steps	Installation Methods	Products & Mix Ratios	Theore	tical Coverage Rates
	Mechanically Prepare and	a. Sandblasting or	MiraPatch RM 1 must be applied to a clean, sound, and		
	Presaturate the Concrete Substrate	b. Shotblasting or	mechanically prepared concrete substrate, as per ICRI's		N/A
1		c. Diamond grinding or	Technical Guideline No.03732, "Selecting and Specifying		
	Note: Minimum (CSP) concrete surface profile	d. Other similar and approved	Concrete Surface Preparation". Concrete substrate		
	of CSP-4 or higher is required depending on	mechanical methods.	should be (SSD) Saturated Surface Dry with no standing		
	substrate conditions & coating requirements.	e. Saturate with potable water	water at the time of application.		
	Prime Concrete Substrate	a. Dip and Roll or	Miracote MPC Liquid Catalyst	500 SF/Gal	
2		b. Spray and broom or	Dilute 1:1 Potable Water		
		c. Spray and backroll or			
		d. Hudson-type spray alone			
	Trowel Apply and Finish MiraPatch RM 1	a. Hand Trowel or	Blend: MiraPatch RM 1 Liquid and MiraPatch RM 1 Powder	Yield:	<b>1.20</b> CF/Unit
	Feather to 3"	b. Screed	Mix Ratio: (2) Gal Liquid to (3) 50 LB Bag	Covers:	115.4 SF @ 1/8"
					57.6 SF @ 1/4"
3	Note: For best results, before placement of				28.8 SF @ 1/2"
	the MiraPatch RM 1 mortar a scrub coat can be				14.4 SF @ 1"
	applied into the primed substrate while still				7.2 SF @ 2"
	wet. MiraPatch RM 1 must be placed before				4.8 SF @ 3"
	scrub coat dries.				
	Depths 3/4" and Greater	a. Hand Trowel or	Blend: MiraPatch RM 1 Liquid and MiraPatch RM1 Powder	Yield:	<b>1.40</b> CF/Unit
	Trowel Apply and Finish MiraPatch RM 1	b. Screed	Mix Ratio: 2 Gal. Liquid to (3) 50 LB Bag	Covers:	22.4 SF @ 3/4"
	Extended with Aggregate		Extend: With 20 LBS of 1/4" Pea Gravel or		16.8 SF @ 1"
4			Extend: With 20 LBS of 3/8" Pea Gravel (> 1" depth)		12.6 SF @ 1.5"
	Note: Aggregates must be uniform in size,				8.4 SF @ 2"
	washed, clean, and can be in bags or bulk.				7 SF @ 2.5"
	As per ACI Guidelines, aggregate size should		Note: Pre-saturate aggregates prior to mixing into		5.6 SF @ 3"
	not be greater than 1/3 of placement depth.		MiraPatch RM 1.		

Note

Prior to starting the application of any Miracote Product or System be sure to read the Installation Guide(s), Product Technical Data Sheets, MSDS and other pertinent documents published by Crossfield Product Corp. for information, including but not limited to, Precautions, Limitations, Disclaimers and Warranties.



Pay special attention to substrate moisture content, physical condition of the substrate, method(s) of surface preparation, surface restoration, detailing of cracks, joints, transitions and terminations, and any applicable specifications. Review carefully for unknown site conditions or defects.

The theoretical coverage rates stated in the Installation Guides are for estimating purposes only. Factors, such as, allowance for material waste, unusual or abnormal substrate conditions and other unforeseen job site conditions that may affect actual product yields are the responsibility of the installer.