

Pourable, cement-based, non-shrinking, quick-setting anchoring cement

SPECROCK is a one-component, waterproof, non-shrinking, Portland cement-based anchoring cement that sets hard in 12-15 minutes. It expands as it sets and locks into the surrounding concrete.



✓ Benefits

- Quick setting; sets hard in 12-15 minutes; speeds production
- Rapid high strength up to 2000 psi. in 1 hour at 72°
- Controlled expansion as it sets
- Nonmetallic; maintains volume stability over time
- Waterproof, resistant to freeze/thaw provides durable, long-lasting applications
- Flowable, and pourable mixture; user friendly application



Usage

- Anchoring bolts
- Reinforcing rods
- Columns
- Railings
- Fences
- Bolts
- Small machines
- Hand rails
- Bridge railings
- Posts
- Signs
- Pulleys and motors



Packaging

- 50 lb (22.7 kg)

TYPICAL TEST DATA

Compressive Strength (ASTM C 109)	
1-hour after set	2000 psi
1 day	5000 psi
28 days	8000 psi
Expansion (ASTM C 157) moist cure = .05%	
Flexural Strength (ASTM C 78)	
28 days	1250 psi
Pull-Out Strength (NYSDOT)	
#5 Rebar, 7/8" dia hole, 6" deep	11,300 lbs