



EcoStar® C

COMMERCIAL VARIABLE SPEED PUMPS

The industry's most energy efficient, variable speed pump. Available with or without integrated SVRS



COMMERCIAL PUMPS



Hayward EcoStar C is the industry's most energy-efficient variable speed pump. Fully Title 20 compliant with up to eight custom speed and timer functions, the settings can be "locked out" for authorized access only. EcoStar C's advanced hydraulic design moves water more efficiently, operating at lower speeds to minimize noise and save pool operators up to 90% on energy costs.

- Permanent Magnet, Totally Enclosed Fan Cooled (TEFC) motor
- Passcode protection of configuration menus to prevent unauthorized access to timer or speed settings
- Unique on-pump, multi-position digital control interface; control can also be detached and wall mounted for added convenience
- Pump available with integrated VGB-compliant SVRS, features automatic restart
- Industry leading hydraulic design
- NSF/ANSI Standard 50 Certified

EcoStar® C

COMMERCIAL VARIABLE SPEED PUMPS

FEATURES

- Large capacity basket to extend time between cleanings
- Advanced hydraulic design with variable frequency drive affords savings up to 90% on energy costs
- 2" x 2½" union connections
- Interchangeable bases included for ease of installation with preexisting pipe work



- Integrated VGB-compliant SVRS model available, featuring automatic restart to mitigate nuisance tripping
- Fully programmable, digital control with 24-hour clock, 8 custom speed and timer functions
- Passcode "lock-out" access to key speed and timer configuration settings
- Unique, multi-position on-pump orientation for ultimate convenience, or detach and wall mount
- Easy-to-read display of status e.g. pump speed and power consumption through transparent plastic cover (black cover for outdoor installation included as standard)
- Permanent Magnet, Totally Enclosed Fan Cooled (TEFC) motor for maximum efficiency and reliability



NSF and ETL certified




VGB-compliant SVRS model features automatic restart




Energy efficiency runs in the family

DIMENSIONS



TECHNICAL SPECIFICATIONS AND PERFORMANCE DATA



EcoStar C runs efficiently in all of these ranges.

Part Number	Description	Speed Range	Voltage	Carton Quantity
HCP3400VSP	EcoStar C	600-3450 RPM	230V Single Phase	1
HCP3400VSPVR	EcoStar C SVRS	1000-3450 RPM	230V Single Phase	1

FEATURES

Convenient Multi-Function, Multi-Position, Detachable Digital Control Interface

Option 1

Control interface can be rotated on the pump for convenient access and viewing.



Option 2

For ultimate flexibility detach control interface and wall-mount using included mounting kit and communication cable.

