

CAT 1000® AUTOMATED pH CONTROLLER

Precise, Automated pH Control





CAT 1000 Automated pH Controller

Most cases of red eyes and itchy skin after pool use are actually caused by poor pH maintenance. With the CAT 1000, pH levels in your pool are continuously monitored and adjusted so the water is always ready for enjoyment. Chlorine is also most effective in keeping water safe when pH is optimally maintained.

Thousands of commercial swimming pools, spas, water parks and aquatic exhibits count on CAT Controllers each day to meet their water quality requirements. Maintaining proper pH protects the costly pool surface and equipment, extending service life while reducing repairs and warranty issues.

- The perfect enhancement for salt-chlorine systems
- Protect your investment
- Spend more time enjoying your pool instead of making routine pH adjustments



THE TOTAL SYSTEM

Combine the CAT 1000 pH Controller with a CAT ${\rm Co}_2$ system or acid feed pump tank combo for a complete pH automation system.

- Advanced microprocessor-based design
- Factory-assembled on PVC backboard with flow cell and flow sensor
- Long-life, low-maintenance sensors
- Five-year comprehensive warranty and technical support

CAT 1000 Technical Specifications

Display Range:	рН	0.0 - 9.9
Setpoint Range:	рН	7.0 - 8.0
Default Setting:	рН	7.5
Calibration Range:	pН	2.0 pH +/-
Control Accuracy:	рH	0.1 pH
Mode Selections:	pH Feed	Auto/Off/Manual
	pH Selection	Acid/Base
	pH Mode	Auto/Set/Calibrate
Safety System:	рН	Audible & Visual Alarms
	Controller Unit	Diagnostic Self Test
	Required	Flow Sensor
	Optional	Remote Alarm
pH Sensor:	Casing Material	Molded ABS
	Junction Type	Teflon Reference

Power Input: 120/240 Volt AC, 10 AMP 50/60 Hz Outputs: pH Feed 4 Amp / 120 VAC 4 Amp / 240 VAC 1 Amp / Dry Contact Remote Alarm 1 Amp / Dry Contact Optional Equipment: Chemical and Acid Feed Systems 5 year comprehensive warranty and technical support / 2 year warranty on sensors			
Power Input: 120/240 Volt AC, 10 AMP 50/60 Hz Outputs: pH Feed 4 Amp / 120 VAC 4 Amp / 240 VAC 1 Amp / Dry Contact 1 Amp / Dr	pH Sensor:	Wet End	½" NPT
Outputs: pH Feed 4 Amp / 120 VAC 4 Amp / 240 VAC 1 Amp / Dry Contact 2 Amp / Dry Contact 3 Amp / Dry Contact 4 Amp / Dry Contact 5 year comprehensive warranty and technical		Connector	Shielded BNC
Outputs: pH Feed 4 Amp / 120 VAC 4 Amp / 240 VAC 1 Amp / Dry Contact 1 Amp / Dry Contact 1 Amp / Dry Contact Chemical and Acid Feed Systems 5 year comprehensive warranty and technical	Power Input:	120/240 Volt AC,	
4 Amp / 240 VAC 1 Amp / Dry Contact 2 Amp / Dry Contact 3 Amp / Dry Contact 4 Amp / Dry Contact 5 year comprehensive warranty and technical		10 AMP 50/60 Hz	
1 Amp / Dry Contact 2 Amp / Dry Contact 3 Amp / Dry Contact 4 Amp / Dry Contact 5 year comprehensive warranty and technical	Outputs:	pH Feed	4 Amp / 120 VAC
1 Amp / Dry Contact 1 Amp / Dry Contact 1 Amp / Dry Contact 2 Optional Equipment: Chemical and Acid Feed Systems 5 year comprehensive warranty and technical			4 Amp / 240 VAC
Remote Alarm 1 Amp / Dry Contact Optional Equipment: Chemical and Acid Feed Systems 5 year comprehensive warranty and technical			1 Amp / Dry Contact
Optional Equipment: Chemical and Acid Feed Systems 5 year comprehensive warranty and technical			1 Amp / Dry Contact
Feed Systems 5 year comprehensive warranty and technical		Remote Alarm	1 Amp / Dry Contact
	Optional Equipment:		
	, ,	,	