

Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication
Standard, 29 CFR 1910.1200.
Standard must be consulted for
specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health
Administration (Non-Mandatory
Form) Form Approved OMB No.
1218-0072

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

IDENTITY/TRADE NAME (as used on Label and List):

CLI Thinset Sanded

GENERIC NAME:

SECTION I : IDENTIFICATION

MANUFACTURER'S NAME: C.L. Industries	EMERGENCY TELEPHONE NUMBER: 1-800-222-1222
ADDRESS (NUMBER, STREET, CITY, STATE and ZIP CODE): 8188 S. Orange Ave.	TELEPHONE NUMBER FOR INFORMATION: 800-333-2660 REVISION DATE: 8/18/2014 REPLACES: NA
Orlando, FL 32809	SIGNATURE OF PREPARER (optional) <i>C. Rodriguez</i>

To Purchasers/Users: This MSDS contains important safety, health and environmental information. Federal regulations require that employers make this information available to their employees. If you are a reseller of this product, you should supply a copy of this MSDS to purchasers.

SECTION II : HAZARD(S) IDENTIFICATION**EMERGENCY OVERVIEW:****POTENTIAL HEALTH EFFECTS**

ROUTES OF HAZARD	BASIS FOR DETERMINATION
Exposure determination: Inhalation	Prolonged inhalation of excessive silica dust may reduce lung function.
EFFECTS OF ACUTE OVEREXPOSURE:	No acute effects.
EFFECTS OF CHRONIC OVEREXPOSURE:	Long term overexposure to high concentrations of this dust without the use of a dust mask may reduce respiratory function in some individuals.

MEDICAL CONDITION AGGRAVATED BY EXPOSURE:	Unknown
EYES AND SKIN:	No special precautions. Flush with water for 15 minutes.
INHALATION AND INGESTION:	No special precautions.

SECTION III : COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL DESCRIPTION

MATERIAL	CAS NO.	OSHA PEL: MG/M3	ACGIH TLV MG/M3
Portland Cement	65977-15-1	5	10
Silica	14808-60-7	0.1	0.1
Clay	132-58-7	5	10

NOTE: Cement may contain very small quantities of hexavalent chromium and alkaline metal oxides, such as calcium oxide.

The components of this product are in compliance with the chemical notification requirements of TSCA. This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

SECTION IV : FIRST AID MEASURES

EYES:	Irrigate eyes with continuously with gentle flowing lukewarm water or at specified eyewash stations for at least 15 minutes. Seek medical attention.
SKIN:	Wash exposed skin with soapy water. If rash or irritation occur, seek medical attention immediately.
INHALATION:	Remove from exposure into fresh air, seek medical attention.

SECTION V : FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: NA

Flammable Limits: NA

LEL:	NA
UEL:	NA
SUITABLE EXTINGUISHING MEDIA:	NONE
UNUSUAL FIRE & EXPLOSION HAZARDS:	NONE
SPECIAL FIRE FIGHTING INSTRUCTIONS:	NONE

SECTION VI : ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAK PROCEDURES: Material is not classified as a toxic pollutant or a hazardous substance under Section 307 and 311 of the Clean Water act. Accidental releases can be cleaned up by sweeping, vacuuming, or flushing with water.

SECTION VII : HANDLING AND STORAGE

Handling & Storage: NA

SECTION VIII : EXPOSURE CONTROL/PERSONEL PROTECTION

VENTILATION: Use sufficient general area ventilation. Local exhaust may be necessary where Threshold Limit Values (TLV's) are exceeded or dusty conditions exist.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Recommended

GLOVES: Recommended

OTHER: None

RESPIRATORY PROTECTION: For dusty conditions use a dust mask approved by NIOSH

SECTION IX : PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Grayish

COLOR: Grayish

VAPOR PRESSURE: NA

VAPOR DENSITY (Air-1): NA

SOLUBILITY IN WATER: Negligible

SPECIFIC GRAVITY: 2.8

EVAPORATION RATE: NA

BOILING POINT: 4046 degree F

ODOR: Odorless

PH: 12

SECTION X : STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY: Reacts with acids to liberate CO2.

HAZARDOUS DECOMPOSITION: None

HAZARDOUS POLYMERIZATION: None

SECTION XI : TOXICOLOGICAL INFORMATION

Not Available

SECTION XII : ECOLOGICAL INFORMATION

Not Available

SECTION XIII : DISPOSAL CONSIDERATIONS

Waste Disposal: Material is not classified as a hazardous waste under RCRA Section 3001. Use normal solid waste disposal procedures which are in compliance with Federal, State and Local Regulations.

SECTION XIV : TRANSPORTATION INFORMATION

D.O.T.: NA

IATA: NA

SECTION XV : REGULATORY INFORMATION

Not Available

SECTION XVI : OTHER INFORMATION

None