

POOL WATER CHEMISTRY

It is necessary for the longevity of the **KRYSTALKRETE** finish and as a condition of this warranty that the following chemical parameters are maintained:

CL	1.0 - 3.0	ppm
pH	7.4 - 7.6	
Total Alkalinity (TA)	80 - 100	ppm
Calcium Hardness (CH)	200 - 400	ppm
Cyanuric Acid	less than 50	ppm
Sequest	12	ppm

In areas where calcium levels exceed normal parameters, alkalinity and pH adjustments are required. The initial fill water is the most important water that the pool will receive. The initial fill water must be tested, recorded and adjusted to the above parameters before it has an opportunity to affect the new **KRYSTALKRETE** finish.

WARRANTY CLAIM PROCEDURES

To initiate a warranty claim notify C.L. Industries, Inc. at P.O. Box 593704, Orlando, FL 32859-3704. Prior to an inspection, C.L. Industries, Inc. must receive by certified mail a brief note describing the complaint and photocopies (do NOT send the originals) of the following:

- Warranty as completed at time of application.
- Original "return receipt" as completed at time of application.
- Copies of monthly (or more frequent) results of water chemistry analysis done by a commercial water chemical retailer.

Upon receipt of the above, C.L. Industries, Inc. will schedule an inspection. Any replacement material will be shipped as described in paragraph 5 of this warranty.