

## CHEM LINK

### Construction & Maintenance

Telephone: 800-826-1681

Fax: 269-679-4448

353 E. Lyons Street

Schoolcraft, MI 49087

[www.chemlink.com](http://www.chemlink.com)

Last Revision: 02/02/17

Document No. DS1233

### Product Description

**NovaLink SL** is a self-leveling, moisture curing sealant, designed for application on horizontal joints in concrete construction such as driveways, sidewalks, plaza decks, balconies, stairwells, parking structures, roof decks, and surrounding fountains and swimming pools. **NovaLink SL** cures rapidly to a solid rubber seal that can accommodate 25% joint movement. Its unique polyether cure chemistry allows **NovaLink SL** to be installed on damp concrete or in damp weather conditions without "outgassing" or forming CO<sub>2</sub> bubbles, as urethane sealants often do. Its excellent self leveling properties and smooth finish allow **NovaLink SL** to be installed without tooling. The elimination of masking tape and tooling results in a significant reduction in labor. **NovaLink SL** is solvent free and will not shrink. Its excellent adhesion to clean masonry or concrete allows it to be installed without a primer in most joints smaller than 1/2 inch wide.

### Applicable Performance Standards

- ASTM C920, Type S, Grade P, Class 25, Uses T<sub>2</sub>, M, & O
- Federal Specification TT-S-00230-C Type I, Class B
- Corps of Engineers CRD-C-541, Type I, Class B
- Canadian Standards Board CAN 19, 13-M82

### Regulatory Compliance

- Conforms to OTC Rule for Sealants
- Meets requirements of California Regs: CARB and SCAQMD
- This product does not contain cancer causing chemicals listed in California Proposition 65.
- Conforms to USDA Requirements for Non-food Contact

### Green Standards:

- LEED 2.2 for New Construction and Major Renovations: Low Emitting Materials (Section 4.1) 1 Point
- NAHB Model Green Home Building Guidelines: 5 Global Impact Points
- VOC Content: less than 16 grams / liter ASTM D2369 EPA Method 24 (tested at 240°F / 115°C)



### Advantages

- Solvent free, 100% solids will not shrink
- 30 minute skin over
- No outgassing on damp surfaces
- Color stability, will not suntan
- Paintable within 24 hours (See limitations)
- +/- 25% joint movement

### Colors

Stone, Gray, Black & White

\* Color matching is available in batch quantity only

### Packaging

- 10.1 oz (300 ml)  
24 cartridges/carton, 45 cartons/pallet
- 20 oz (600 ml)  
12 sausages/carton, 40 cartons/pallet
- 28 oz (825 ml)  
12 cartridges/carton, 40 cartons/pallet
- 2 Liter Pouch - 68 oz (2011 ml)  
4 pouches/carton, 45 cartons/pallet
- 2 and 5 gallon pails or 50 gallon drums available by special order