

CHEM LINK

Construction & Maintenance

Telephone: 800-826-1681

Fax: 269-679-4448

353 E. Lyons Street

Schoolcraft, MI 49087

www.chemlink.com

Last Revision: 04/13/16

Document No. DS1005

Product Description

WallSecure is a fast setting wall and block adhesive with excellent adhesion to drywall, wood, metal, concrete, landscape blocks, capstones, and other masonry substrates.

WallSecure is 100% solids and is ideal for filling gaps or forming bonds on irregular surfaces without shrinking.

WallSecure is a solvent free, non-flammable, moisture curing adhesive that complies with all OSHA, State, Local and Federal air quality regulations. This adhesive is non-carcinogenic and contains no substances listed on California Proposition 65.

Basic Uses*
Landscape Blocks
Capstones
Drywall to Wood Assemblies
EPS, XPS & ISO Foam Insulation Board
Wood to Metal

**Test and evaluate to ensure adequate adhesion*

Regulatory Compliance

- Conforms to OTC Rule for Adhesives
- Meets requirements of California Regs: CARB and SCAQMD
- This product does not contain cancer causing chemicals listed in California Proposition 65
- Conforms to USDA Requirements for non-food contact
- Conforms to ASTM C557

Green Standards:

- LEED 2.2 for New Construction and Major Renovations: Low Emitting Materials (Section 4.1) 1 Point
- NAHB Model Green Home Building Guidelines: 5 Global Impact Points
- VOC Content: less than 20 grams / liter ASTM D2369 EPA Method 24 (tested at 240°F / 115°C)

Advantages

- Solvent free, 100% solids, will not shrink
- No outgassing on damp surfaces
- Paintable within 24 hours
- Can be applied at temperatures down to 32°F (0°C)
- Fast Setting
- High Adhesion
- Non-carcinogenic



Color
Tan

Packaging

- **10.1 oz (300ml) cartridges**
24 cartridges/carton, 45 cartons/pallet
- **28 oz (825ml) cartridges**
12 cartridges/carton, 40 cartons/pallet
- **2 and 5 gallon pails, or 50 gallon drums**
available by special order



American
Architectural
Manufacturers
Association



NATIONAL
ROOFING
CONTRACTORS
ASSOCIATION
MEMBER

