

# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000013833  
**Product identifier** **16 OZ CLUB CAR WAX ALL LB 12PK**  
**Company information** CLUB CAR  
2044 FORWARD AUGUSTA DRIVE  
AUGUSTA, GA 30906 United States  
**Company phone** General Assistance 706-863-3000  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Recommended use** Coating  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Acute toxicity, inhalation Category 4  
Germ cell mutagenicity Category 1B  
Aspiration hazard Category 1  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.  
**Response** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.  
**Storage** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
Propane		74-98-6	2.5 - 10
Other components below reportable levels			60 - 80

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills in original containers for re-use. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Use only outdoors or in a well-ventilated area. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Provide adequate ventilation. Avoid breathing mist or vapor.
Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Keep in a cool place. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
		1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Explosion-proof general and local exhaust ventilation.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Hand protection</b>	Wear protective gloves.
<b>Skin protection</b>	
<b>Other</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	191.44 °F (88.58 °C) estimated
<b>Flash point</b>	-156.0 °F (-104.4 °C) Propellant estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	2.2 % estimated
<b>Flammability limit - upper (%)</b>	9.5 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	50 - 70 psig estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.892 g/cm3 estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.

<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	392 °F (200 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.73 g/cm3 estimated
<b>Flammability class</b>	Flammable IB estimated
<b>Heat of combustion</b>	12.4 kJ/g estimated
<b>Heat of combustion (NFPA 30B)</b>	12.32 kJ/g estimated
<b>Percent volatile</b>	74.79 % estimated
<b>Specific gravity</b>	0.892 estimated
<b>VOC (Weight %)</b>	29.62 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Fluorine. Chlorine. Nitrates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.
<b>Inhalation</b>	Not available.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Direct contact with eyes may cause temporary irritation. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
---	--

### Information on toxicological effects

<b>Acute toxicity</b>	Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
-----------------------	---

Components	Species	Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes

Components	Species	Test Results
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	Not available.	
Germ cell mutagenicity	Not available.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	

## 12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.		
Product	Species		Test Results
16 OZ CLUB CAR WAX ALL LB 12PK (CAS Mixture)			
Aquatic			
Fish	LC50	Fish	12.2612 mg/l, 96 hours estimated
Acute			
Algae	IC50	Algae	2033.7108 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia	52876.4805 mg/L, 48 Hours estimated
Components	Species		Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octanol / water (log Kow)			
Propane		2.36	
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

### IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

### IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

#### Safe Drinking Water Act (SDWA)

Not regulated.

### US state regulations

#### US. Massachusetts RTK - Substance List

Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Propane (CAS 74-98-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Propane (CAS 74-98-6)

**US. Rhode Island RTK**

Propane (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Diethanolamine (CAS 111-42-2)

Listed: June 22, 2012

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision****Issue date** 05-14-2015**Version #** 01

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.