

ARCHETECTURAL GRADE SERIES

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

FAX.

(800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

PRODUCT #: CL-533B-GM

Directional Lights

Cast Brass

Fixture Specifications:

Housing & Shroud: Corrosion Resistant Cast Brass.

GM- Gun Metal. Natural toning process. Finish:

> GM finish will vary due to artistic process. Also available in AB- Antique Bronze finish

Lens: Frosted and heat resistant tempered flat glass,

supplied with extra clear glass lens, linear glass lens,

and honeycomb louver.

Socket: Top grade fixed ceramic bi-pin socket.

Lamp: 12V, T3 halogen, 35W max. L-20T3 (20w) standard.

> LED lamps available in 2W and 2.5W, with 2700K-warm white or 3000K-cool white color temperature. Xenon

and halogen lamps also available.

Wiring: Fixture is prewired with a 5-ft 18-2 SPT2-W direct

burial cord. Wire connector available seperately. Universal connector (CX-839) or silicone filled wire nut (CX-854) may be ordered to Corona Lighting.

Gasket: Silicone gasket for water tight sealing

Knuckle: Adjustable cast brass knuckle with thumb screw

and 1/2" NPT threaded male hub on bottom.

Mounting Spike: Standard injection molded spike with ½" NPT

threaded female hub.

Electrical Notes: A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for LED lamps are 8V to 21V. Proper grease/lubricant is suggested on threaded


parts during installation process.

Warranty: Limited lifetime warranty on fixture housing against

manufacturer's defects.







AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

1		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-EDT3-2W	2	360°	200	2700K	25,000	20 Watt
L-EDT3-2.5W	2.5	180°	240	2700K	25,000	35 Watt
L-EDT3-2W-3K	2	360°	210	3000K	25,000	20 Watt
L-EDT3-2.5W-3K	2.5	180°	250	3000K	25,000	35 Watt
L-EDT3-AM	2	360°	170	2000K	25,000	20 Watt

AVAILABLE HALOGEN LAMPS		BEAM		COLOR &	RATED
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS
L-10T3	10		120	2950K	2,000
L-20T3	20		300	2950K	2,000
L-10T3/SC	10		120	2950K	2,000
L-10T3/SC	20		300	2950K	2,000

AM- Amber color For more additional Lamps, and accessories visit Coronalighting.com JOB INFORMATION

DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

When ordering a halogen or xenon lamp add lamp number to the product number. If you are ordering LED lamps you should follow the format below:

• CL - product # - lamp - wattage CL - 533B-GM - L-EDT3 - 2W-3K

Example: CL-533B-GM-L-EDT3-2W-3K

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.