

## **SPECIFICATION SHEET**

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

1

CT # : C ecificatio ninum Aluminum pipe w is also available ester UV powder <b>BZ- Bronze</b> r tempered glass akler water protec grade fixed cerar lamp access. T3, 20W max. lable in LED (2W Lamp guide belo	vith ½" NPT or e. r coated, avai s, cover over l ction. mic bi-pin soc V & 2.5W) or v	ilable in <b>BK-E</b> lamp providir cket. Easy too without lamp.	Black ng ol	Wiring Mounti	ng Spike: cal Notes:	cord.Wire connector connector ( <b>CX-839</b> ), ( <b>CX-LOC</b> ) or silicone available from Coron Standard injection mo threaded female hub. A remote 12V transfo ordered to Corona Lig Voltage range for LEI Proper grease/lubrica threaded parts during	olded spike with ½" NPT o. ormer required, may be ighting seperately. Voltage D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
ninum Aluminum pipe w is also available ester UV powder <b>BZ- Bronze</b> r tempered glass ikler water protec grade fixed cerar lamp access. T3, 20W max. lable in LED (2W	with $\frac{1}{2}^{"}$ NPT or e. r coated, avai s, cover over l ction. mic bi-pin soc V & 2.5W) or v ow for more ir $\frac{1}{1\frac{1}{2}}$	ilable in <b>BK-E</b> lamp providir cket. Easy too without lamp nformation.	Black ng ol	Mounti Electri	ng Spike: cal Notes:	cord.Wire connector connector ( <b>CX-839</b> ), ( <b>CX-LOC</b> ) or silicone available from Coron Standard injection mo threaded female hub. A remote 12V transfo ordered to Corona Lig Voltage range for LEI Proper grease/lubrica threaded parts during <b>Five (5) year</b> warrant	sold seperately Universal quick locking wire connector e filled wire nut ( <b>CX-854</b> ) is na Lighting. olded spike with ½" NPT o. ormer required, may be ighting seperately. Voltage D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
Aluminum pipe w i is also available ester UV powder <b>BZ- Bronze</b> r tempered glass ikler water protec grade fixed cerar lamp access. T3, 20W max. lable in LED (2W	e. r coated, avai s, cover over l ction. mic bi-pin soc V & 2.5W) or v ow for more ir $\sqrt{\frac{1}{1\frac{1}{2}}}$	ilable in <b>BK-E</b> lamp providir cket. Easy too without lamp nformation.	Black ng ol	Mounti Electri	ng Spike: cal Notes:	cord.Wire connector connector ( <b>CX-839</b> ), ( <b>CX-LOC</b> ) or silicone available from Coron Standard injection mo threaded female hub. A remote 12V transfo ordered to Corona Lig Voltage range for LEI Proper grease/lubrica threaded parts during <b>Five (5) year</b> warrant	sold seperately Universal quick locking wire connector e filled wire nut ( <b>CX-854</b> ) is na Lighting. olded spike with ½" NPT o. ormer required, may be ighting seperately. Voltage D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
<b>BZ- Bronze</b> r tempered glass ikler water protect grade fixed cerar lamp access. T3, 20W max. lable in LED (2W	s, cover over 1 ction. mic bi-pin soc V & 2.5W) or v ow for more ir $1\frac{1}{\sqrt{2}}$	lamp providir cket. Easy too without lamp. nformation.	ng ol	Electri	cal Notes:	Standard injection mo threaded female hub. A remote 12V transfo ordered to Corona Lig Voltage range for LEI Proper grease/lubrica threaded parts during <b>Five (5) year</b> warrant	olded spike with ½" NPT o. ormer required, may be ighting seperately. Voltage D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
ukler water protect grade fixed cerar lamp access. T3, 20W max. lable in LED (2W	ction. mic bi-pin soc V & 2.5W) or v ow for more in $1\frac{1}{12}$	cket. Easy too without lamp nformation.	ol			A remote 12V transfo ordered to Corona Lig Voltage range for LEI Proper grease/lubrica threaded parts during Five (5) year warrant	ormer required, may be ighting seperately. Voltage D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
lamp access. T3, 20W max. lable in LED (2W	V & 2.5W) or v ow for more in $\frac{1}{1}\frac{1}{1/2}$	without lamp. information. $ -3^{1/2}"- $		Warrar	ıty:	Voltage range for LEL Proper grease/lubrica threaded parts during <b>Five (5) year</b> warrant	D lamps are 8V to 21V. ant is suggested on g installation process. ty on fixture housing and stem
Lamp guide beid	$\frac{1}{1}\frac{\frac{1}{1/2}}{\frac{1}{1}}$	<b>←3<sup>1</sup>⁄2"→</b>		Warrar	nty:		
	<b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b> <b>1</b>						
CL-640-BK 3" Standard tem Shown		<u>↓</u>					CL-640-BZ-12 12" Stem (Optional) Shown
-	BEA	AM	COLOR &	RATED	HALOGEN	I	DATE:
2 2.5 2 2.5 2	360° 180° 360° 180° 360° visit Coronalighting	200 240 210 250 170	2700K 2700K 3000K 3000K 2000K	25,000 25,000 25,000 25,000 25,000	20 Watt 35 Watt 20 Watt 35 Watt 20 Watt	JOB NAME & ADDR PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WAT TRANSFORMER: CONTRACTOR: SPECIFIER:	
	" Standard em Shown D LAMPS (Core 2.5 2.5 2 2.5 2 2.5 2	r Standard em Shown D LAMPS (Corona LED lamps ha <u>BE</u> <u>WATTS SPREAD</u> 2 360° 2.5 180° 2 360° 2.5 180° 2 360° 2 360°	8 Y2       8 Y2         D LAMPS (Corona LED lamps have a five (5) yea         BEAM         WATTS       SPREAD       LUMEN         2       360°       240         2       360°       210         2.5       180°       250         2       360°       170	8 Standard em Shown       8 /2"       2W         D LAMPS (Corona LED lamps have a five (5) year limited warra served by the served by the	* Standard em Shown       8 ½ *       Lument Let Let Let Let Let Let Let Let Let Le	Standard em Shown       8 ½ 2 4       Luc	* Standard em Shown       8 // 2"       LLE LU 2W & 2.5W         D LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)       JOB INFORMA         WATTS       SPREAD       LUMEN       COLOR & RATED HOURS       HALOGEN EQUIVALENT         2       360°       200       2700K       25,000       20 Watt         2       360°       210       3000K       25,000       35 Watt         2       360°       210       3000K       25,000       35 Watt         2       360°       170       2000K       25,000       20 Watt         Diss, and accessories visit Coronalighting.com       LMP TYPE & WAT       TRANSFORMER:         CONTRACTOR:       SPECIFIER:       SPECIFIER:

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



## **Cable Connectors**

CX-854Direct Burial Silicone Filled Wire Nut, TanCX-858Speedy Cable Connector, Supply Cable up to 10-2, BlackCX-839Universal cable connector, Supply cable up to 8-2,<br/>one/Pack BlackCX-LOCQuick-Locking Silicone Filled Wire Connector, 25 Sets (50<br/>per Pack)



