



THREADED EXTERNALLY COATED TRANSITION FITTINGS: PE2708, MTP x IPS, DR11

- Meets ASTM D2513
- Approval: ASTM F1973 (indicated with *)
- Approval: IAPMO (indicated with *)
- Certified to CSA B137.4 (indicated with *)
- Approval: ANSI B1.20.1 (indicated with *)
- Approval: CAT-1
- Protective sleeves are available upon request.
- Call for availability of other sizes and dimensions.
- GF Central Plastics offers thousands of different riser configurations. The configurations listed here are standard stocking sizes.

Size	GF Code	weight (lb)	L (inch)	L2 (inch)	z (inch)	Minimum Order Qty
0.75" MPT x 0.75" IPS	360 002 546	0.8	17.13	5.31	11.81	36
0.75" MPT x 0.75" IPS	360 013 807	2.0	29.81	18.00	11.81	30
1" MPT x 0.75" IPS	360 002 550	1.3	17.12	5.31	11.81	25
1" MPT x 1" IPS	360 002 555	1.2	17.33	5.52	11.81	25
1.25" MPT x 1.25" IPS	360 003 778	1.7	17.81	5.88	11.94	16
1.5" MPT x 1.5" IPS	360 013 828	4.9	30.00	18.00	12.00	15
1.5" MPT x 1.5" IPS	360 002 563	2.4	18.19	6.19	12.00	12
2" MPT x 2" IPS	360 002 565	3.0	18.38	6.22	12.16	16
4" MPT x 4" IPS	360 003 779	12.0	19.13	7.06	12.06	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>