

HYDROSEAL

PROFESSIONAL FEATURES

- CPVC Bodies Awarded NSF International Seal
- Serviceable Clear Lid with Lock Nut
- Corrosion Proof Pin
- Longer Sockets for Better Glue Joints
- Silicone Check Seal Never Requires Lubrication

CORROSION RESISTANT MODELS

- Protects Systems with a Chlorinator or Brominator
- Ceramic Pin for Extra Corrosion Protection
- Hastelloy Spring for High Stress and Corrosive Environments



THREAD-ON STYLE
HIGH-TEMP CPVC



THREAD-ON STYLE
WHITE PVC



180° STANDARD STYLE
HIGH-TEMP CPVC



90° STANDARD STYLE
HIGH-TEMP CPVC



UNION PORT STANDARD STYLE
HIGH-TEMP CPVC

ORDERING GUIDE

HYDROSEAL SERVICEABLE CHECK VALVES

CMP P/N	SPRING	MAX FLOW	MAX PSI	DESCRIPTION	PORTS
25830-150-000	2 POUND	100gpm	50psi	THREAD-ON STYLE, BLACK CPVC (NSF)	1.5" SOCKET × 2" SPIGOT
25830-200-000	2 POUND	100gpm	50psi	THREAD-ON STYLE, BLACK CPVC (NSF)	2" SOCKET × 2.5" SPIGOT
25830-450-000	1/4 POUND	100gpm	50psi	THREAD-ON STYLE, BLACK CPVC (NSF)	1.5" SOCKET × 2" SPIGOT
25830-500-000	1/4 POUND	100gpm	50psi	THREAD-ON STYLE, BLACK CPVC (NSF)	2" SOCKET × 2.5" SPIGOT
25830-350-000	2 POUND	100gpm	50psi	CORROSION RESISTANT, THREAD-ON STYLE, BLACK CPVC (NSF)	1.5" SOCKET × 2" SPIGOT
25830-400-000	2 POUND	100gpm	50psi	CORROSION RESISTANT, THREAD-ON STYLE, BLACK CPVC (NSF)	2" SOCKET × 2.5" SPIGOT
25830-360-000	2 POUND	100gpm	50psi	CORROSION RESISTANT, THREAD-ON STYLE, WHITE PVC	1.5" SOCKET × 2" SPIGOT
25830-410-000	2 POUND	100gpm	50psi	CORROSION RESISTANT, THREAD-ON STYLE, WHITE PVC	2" SOCKET × 2.5" SPIGOT
25830-704-000	2 POUND	125gpm	50psi	180° STANDARD STYLE, BLACK CPVC	1.5" SOCKET × 2" SPIGOT
25830-714-000	2 POUND	125gpm	50psi	180° STANDARD STYLE, BLACK CPVC	2" SOCKET × 2.5" SPIGOT
25830-250-000	2 POUND	125gpm	50psi	180° STANDARD STYLE, BLACK CPVC	2.5" SOCKET × 3" SPIGOT
25830-804-000	1/2 POUND	125gpm	50psi	180° STANDARD STYLE, BLACK CPVC	1.5" SOCKET × 2" SPIGOT
25830-814-000	1/2 POUND	125gpm	50psi	180° STANDARD STYLE, BLACK CPVC	2" SOCKET × 2.5" SPIGOT
25830-764-000	2 POUND	125gpm	50psi	90° STANDARD STYLE, BLACK CPVC	1.5" SOCKET × 2" SPIGOT
25830-774-000	2 POUND	125gpm	50psi	90° STANDARD STYLE, BLACK CPVC	2" SOCKET × 2.5" SPIGOT
25830-864-000	1/2 POUND	125gpm	50psi	90° STANDARD STYLE, BLACK CPVC	1.5" SOCKET × 2" SPIGOT
25830-874-000	1/2 POUND	125gpm	50psi	90° STANDARD STYLE, BLACK CPVC	2" SOCKET × 2.5" SPIGOT
25830-724-000	2 POUND	125gpm	50psi	UNION PORT STANDARD STYLE, BLACK CPVC	1.5" SOCKET UNION
25830-734-000	2 POUND	125gpm	50psi	UNION PORT STANDARD STYLE, BLACK CPVC	2" SOCKET UNION