Section 1: IDENTIFICATION			
1.1 PRODUCT IDENTIFIER			
Product Name:	All types of concrete blocks, pavers, and other cementitous products.		
Product Code:	Various		
1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE			
Use:	Construction material used in building and hardscape applications.		
1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET			
Name/Address:	Oldcastle Affiliated Companies, 900 Ashwood Parkway Suite 600 Atlanta, GA 30338		
Telephone Number:	866-256-7404		
1.4 EMERGENCY TELEPHONE NUMBER			
Emergency Telephone Number:	1-800-424-9300		
Date of Preparation:	May 22, 2015	<b>Version #:</b> 1.0	
Section 2: HAZARD(S) IDENTIFICATION			

## 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Skin irritation 2 Eye irritation 2A Skin sensitization 1 Carcinogenicity 1A Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

## 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:



Signal Word: Hazard Statement:

Prevention:

Danger

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Respirable dust may contain crystalline silica, known to cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust.

Response:	If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Storage:	Not applicable.
Disposal:	Dispose of unused or unwanted concrete products in accordance with all local, regional, national and international regulations.


## 2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

47 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

## Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

### WHMIS Classification(s):

Class D2A - Carcinogenicity Class D2A - Chronic Toxic Effects Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



WHMIS Signal Word:

WARNING

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### **3.1 MIXTURES**

Ingredient	UN #	H / F/ R / *	CAS No	Wt. %
Coarse aggregate	Not available.	Not available.	Not available.	15 - 60
Portland cement	Not available.	1/0/0	65997-15-1	10 - 30
Ashes (residues)	Not available.	Not available.	68131-74-8	0.1 - 30
Slags, ferrous metal, blast furnace	Not available.	Not available.	65996-69-2	0.1 - 30
Water	Not available.	Not available.	7732-18-5	10 - 30

Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	3 - 7
Ferric oxide	UN1376	1/0/0	1309-37-1	1 - 5
Calcium carbonate	Not available.	1/0/0	1317-65-3	1 - 5
Calcium hydroxide	Not available.	3/0/0	1305-62-0	1 - 5
Silica, amorphous, fumed	Not available.	Not available.	7631-86-9	1 - 5
Admixtures (organic and inorganic)	Not available.	Not available.	Not available.	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

\* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES			
4.1 DESCRIPTION OF THE FIRST AID MEASURE			
Eye:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If eye irritation persists: Get medical advice/attention.		
Skin:	If irritation occurs, flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.		
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.		
Ingestion:	Not a normal route of exposure. If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.		
4.2 MOST IMPORTANT SYMPT	FOMS AND EFFECTS, BOTH ACUTE AND DELAYED		
Eye:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.		
Skin:	Causes skin irritation. Wear gloves when handling product to avoid drying and mechanical abrasion of the skin. May cause sensitization by skin contact.		
Inhalation:	Dust may cause respiratory tract irritation.		
Ingestion:	Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.		
4.3 INDICATION OF ANY IMME	4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED		
Note to Physicians:	Symptoms may not appear immediately.		
Specific Treatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).		
	Section 5: FIRE-FIGHTING MEASURES		
5.1 FLAMMABILITY			

Flammability:

Not flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

## **5.2 EXTINGUISHING MEDIA**

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

## 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

#### **Explosion Data:**

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

## 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

## 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

## 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment:	Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container. Use wet methods, if appropriate, to reduce the generation of dust. Provide ventilation if dust is generated.
	Section 7. HANDLING AND STORAGE

## Section 7: HANDLING AND STORAGE

### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Avoid contact with skin and eyes. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. Use wet methods, if appropriate, to reduce the generation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle with care. When using do not eat or drink. (See section 8)
General Hygiene Advice:	Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	
Storage:	Avoid any dust buildup by frequent cleaning and suitable construction of

the storage area. (See section 10)

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 CONTROL PARAMETERS

#### **Exposure Guidelines**

Occupational Exposure Limits			
Ingredient	OSHA-PEL	ACGIH-TLV	
Coarse aggregate	Not available.	Not available.	
Portland cement	15 mg/m³ (total); 5 mg/m³ (resp)	1 mg/m <sup>3</sup> (no asbestos and <1% crystalline silica, respirable fraction)	
Ashes (residues)	Not available.	Not available.	
Slags, ferrous metal,			
blast furnace	Not available.	Not available.	
Water	Not available.	Not available.	
	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) (resp)) ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) (total))		
Silica, crystalline, quartz	((250)/(%SiO <sub>2</sub> +5) mppcf (resp))	0.025 mg/m³	
Ferric oxide	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup> (iron oxide fume; dust as Fe)	
Calcium carbonate	15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (resp)	10 mg/m <sup>3</sup>	
Calcium hydroxide	15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (resp)	5 mg/m³	
Silica, amorphous, fumed	80 mg/m³/%SiO <sub>2</sub>	10 mg/m <sup>3</sup>	
Admixtures (organic and			
inorganic)	Not available.	Not available.	

#### 8.2 EXPOSURE CONTROLS

Engineering Controls:

When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

#### 8.3 INDIVIDUAL PROTECTIVE MEASURES

**Personal Protective Equipment:** 

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

**Skin Protection:** 

Hand Protection: Wear suitable gloves.

**Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety<br/>Measures:Handle according to established industrial hygiene and safety<br/>practices. Do not eat, smoke or drink where material is handled,<br/>processed or stored. Wash hands carefully before eating or smoking.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Fully cured and hydrated concrete.
Color:	Not available.
Odor:	Odorless.
Odor Threshold:	Not available.
Physical State:	Solid.
pH:	Not available.
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density/Specific Gravity:	Not available.
Solubility:	Insoluble.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Oxidizing Properties:	Not available.
Explosive Properties:	Not available.

## Section 10: STABILITY AND REACTIVITY

## **10.1 REACTIVITY**

No dangerous reaction known under conditions of normal use.

## **10.2 CHEMICAL STABILITY**

Stable under normal conditions of use.

## **10.3 POSSIBILITY OF HAZARDOUS REACTIONS**

No dangerous reaction known under conditions of normal use.

## **10.4 CONDITIONS TO AVOID**

None known.

## **10.5 INCOMPATIBLE MATERIALS**

None known.

#### **10.6 HAZARDOUS DECOMPOSITION PRODUCTS**

None known.

#### Section 11: TOXICOLOGICAL INFORMATION

### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

Likely Routes of Exposure: Skin contact, eye contact, and inhalation.

Symptoms related to physical/chemical/toxicological characteristics:

- **Eye:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- **Skin:** Causes skin irritation. Wear gloves when handling product to avoid drying and mechanical abrasion of the skin. May cause sensitization by skin contact.
- **Ingestion:** Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.
- Inhalation: Dust may cause respiratory tract irritation.

#### Acute Toxicity:

Ingredient	IDLH	LC50	LD50
Coarse aggregate	Not available.	Not available.	Not available.
Portland cement	5000 mg/m <sup>3</sup>	Not available.	Not available.
Ashes (residues)	Not available.	Not available.	Oral > 2000 mg/kg, rat
Slags, ferrous metal, blast furnace	Not available.	Not available.	Not available.
Water	Not available.	Inhalation 90000 mg/m³/4h, rat	Oral >90000 mg/kg, rat Dermal >90000 mg/kg, rabbit
Silica, crystalline, quartz	Ca [25 mg/m <sup>3</sup> (cristobalite, tridymite); 50 mg/m <sup>3</sup> (quartz, tripoli)]	Not available.	Oral 500 mg/kg, rat
Ferric oxide	2500 mg Fe /m <sup>3</sup>	Not available.	Oral >10000 mg/kg, rat
Calcium carbonate	Not available.	Not available.	Oral 6450 mg/kg, rat
Calcium hydroxide	Not available.	Not available.	Oral 7340 mg/kg, rat
Silica, amorphous, fumed	Not available.	Inhalation ≥58.8 mg/l/1h, rat	Oral >5000 mg/kg, rat Dermal >2000 mg/kg, rabbit
Admixtures (organic and inorganic)	Not available.	Not available.	Not available.

Calculated overall Chemical Acute Toxicity Values			
LC50 (inhalation) LD50 (oral) LD50 (dermal)			
> 5 mg/l/4h, rat > 2000 mg/kg, rat > 2000 mg/kg, rabbit			

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Coarse aggregate	Not listed.
Portland cement	G-A4
Ashes (residues)	Not listed.
Slags, ferrous metal, blast furnace	Not listed.
Water	Not listed.

Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
Ferric oxide	G-A4, I-3
Calcium carbonate	Not listed.
Calcium hydroxide	Not listed.
Silica, amorphous, fumed	I-3
Admixtures (organic and inorganic)	Not listed.

\* See Section 15 for more information.

## 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Causes skin irritation.
Serious Eye Damage/Irritation:	Causes serious eye irritation.
Respiratory Sensitization:	Based on available data, the classification criteria are not met.
Skin Sensitization:	May cause an allergic skin reaction.
STOT-Single Exposure:	Dust may cause respiratory tract irritation.
Chronic Health Effects:	
Carcinogenicity:	Respirable dust may contain crystalline silica, known to cause cancer.
Germ Cell Mutagenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	
Developmental:	Based on available data, the classification criteria are not met.
Teratogenicity:	Based on available data, the classification criteria are not met.
Embryotoxicity:	Based on available data, the classification criteria are not met.
Fertility:	Based on available data, the classification criteria are not met.
Fertility: STOT-Repeated Exposure:	Based on available data, the classification criteria are not met. Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
-	Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually
STOT-Repeated Exposure:	Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Section 12	2: ECOLOGICAL INFORM	ATION	
12.1 ECOTOXICITY			
Acute/Chronic Toxicity: No	ecological consideration w	hen used according to directions.	
12.2 PERSISTENCE AND DEGRADABIL	ΙТΥ	-	
Not available.			
12.3 BIOACCUMULATIVE POTENTIAL			
Bioaccumulation: Not	Not available.		
12.4 MOBILITY IN SOIL			
Not available.			
12.5 OTHER ADVERSE EFFECTS			
Not available.			
Section 13	: DISPOSAL CONSIDERA	TIONS	
13.1 WASTE TREATMENT METHODS			
Disposal Method:	This material must be	disposed of in accordance with a	
		This material must be disposed of in accordance with all local, state, provincial, and federal regulations.	
Other disposal recommendations:	Not available.		
Section 1	4: TRANSPORT INFORMA	TION	
14.1 UN NUMBER			
DOT	TDG	NOM-004-SCT2-1994	
Not regulated.	Not regulated.	Not regulated.	
14.2 UN PROPER SHIPPING NAME	-	-	
DOT	TDG	NOM-004-SCT2-1994	
Not applicable.	Not applicable.	Not applicable.	
14.3 TRANSPORT HAZARD CLASS (ES)	1		
DOT	TDG	NOM-004-SCT2-1994	
Not applicable.	Not applicable.	Not applicable.	
14.4 PACKING GROUP			
DOT	TDG	NOM-004-SCT2-1994	
Not applicable.	Not applicable.	Not applicable.	
4.5 ENVIRONMENTAL HAZARDS			
Not available.			
	G TO ANNEX II OF MARPO	DL 73/78 AND THE IBC CODE	
I4.6 TRANSPORT IN BULK ACCORDING Not available.	G TO ANNEX II OF MARPO	DL 73/78 AND THE IBC CODE	

Do not handle until all safety precautions have been read and understood.

## Section 15: REGULATORY INFORMATION

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III Ingredient Section 302 Section 304 CERCLA Section (EHS) TPQ (lbs.) EHS RQ (lbs.) RQ (lbs.) 313 Coarse aggregate Not listed. Not listed. Not listed. Not listed. Portland cement Not listed. Not listed. Not listed. Not listed. Ashes (residues) Not listed. Not listed. Not listed. Not listed. Slags, ferrous metal, blast furnace Not listed. Not listed. Not listed. Not listed. Water Not listed. Not listed. Not listed. Not listed. Silica, crystalline, quartz Not listed. Not listed. Not listed. Not listed. Ferric oxide Not listed. Not listed. Not listed. Not listed. Calcium carbonate Not listed. Not listed. Not listed. Not listed. Calcium hydroxide Not listed. Not listed. Not listed. Not listed. Silica, amorphous, fumed Not listed. Not listed. Not listed. Not listed. Admixtures (organic and inorganic) Not listed. Not listed. Not listed. Not listed.

Mexico: SDS prepared pursuant to NOM-018-STPS-2000.

## State Regulations

#### **California Proposition 65:**

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm which may be released upon sanding/cutting/grinding/drilling.

#### Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Coarse aggregate	Not available.	Not available.
Portland cement	DSL	Yes.
Ashes (residues)	DSL	Yes.
Slags, ferrous metal, blast furnace	DSL	Yes.
Water	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Ferric oxide	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Calcium hydroxide	DSL	Yes.
Silica, amorphous, fumed	DSL	Yes.
Admixtures (organic and inorganic)	Not available.	Not available.

Health:	2
Fire:	0
Reactivity:	0
Health:	2*
Health:	2*
Fire:	0
Physical Hazard:	0

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

;.	
evidence of carcinogenicity in evidence of carcinogenicity in tal animals. rcinogenicity to humans. to humans.	
Section 16: OTHER INFORMATION	

Date of Preparation:		
Expiry Date:		
Version:	1.0	
Revision Date:		

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

## End of Safety Data Sheet