

Otter 8-Lane Scoreboard

This indoor/outdoor LED swimming scoreboard provides wireless scoring capabilities for 8 lanes of swimming, and includes 3-digit EVENT and HEAT. Weather-proof digits and electronics are housed in a powder-coated aluminum chassis, which provides excellent corrosion resistance. Scoreboard is shipped as one piece for ease of handling and installation.

CONTROL CONSOLES

- The integrated internal antenna allows for reliable wireless communication from any WA-2 connected to the **System 6 Timing Console**.
- Data jack located on the bottom or rear of the display for wired RS-232 communication from the **System 6 Timing Console**.
- The integrated internal antenna allows for reliable wireless communication from the **Dolphin Wireless Timing System**.

DIGITS

The high visibility LED digits automatically adjust to ambient light to provide optimal viewing when used with the System 6 Timing Console.

EVENT		HEAT
12		2
COLORADO TIME SYSTEMS		
LN	PL	TIME
1	7	10:03.90
2	5	9:46.63
3	2	9:37.46
4	1	9:37.08
5	3	9:38.52
6	8	10:13.63
7	4	9:42.70
8	6	9:51.46

Part No: MS-0150

Overall size (W x H x D):

4.0' x 5' 10" x 4.25"
(1.2 m x 1.8m x
10.8cm)

Weight: 70 lbs (31.8kg)

Digit sizes: 5" (12.7cm)

Power: 115VAC~230VAC,
50/60Hz, 240W, 14'
power cord with
NEMA 5-15R plug;
available with
international plug (type
F, G, or I) upon request

*Colorado Time Systems is the Official Timing and
Scoring Partner of*



www.coloradotime.com



MS-0150 Specifications

CONSTRUCTION & MOUNTING

- Scoreboard assembly consists of a single 5052-alloy aluminum display chassis with internal digit brackets.
- High-strength polycarbonate digit covers protect digits and antenna from weather and impact.
- Scoreboard is shipped as one piece for ease of handling and installation.
- Various mounting options allow for the display to be mounted directly to a flat wall, corner wall, vertical beam, or portable caddy. Mounting tabs are attached to the board in one of three locations. Simply lift the display into place, where is then easily bolted to the wall or support structure.

SERVICE ACCESS

- All digits and electronic components are accessed through the front-face of the scoreboard.
- Digit covers are secured by two removable end caps.

SIGN PANELS & CAPTIONS


- Various sign panel options are available - contact your sales representative for more information regarding advertising and identification sign panels.
- Vinyl artwork captions (3") are applied directly to polycarbonate digit covers.

OPERATING TEMPERATURES & PRODUCT SAFETY APPROVAL

- -41 - 131° Fahrenheit (-5 - 55° Celsius)
- CETLus, FCC, and RoHS compliant

CUSTOMIZATION OPTIONS AND ACCESSORIES

- Choose from the following powder-coat color options at no additional cost:



- Advertising/identification sign panels
- Add-on video display panels of various sizes
- Decorative accents