POOLECARE

BY DANNER MANUFACTURING

POOL MAIN DRAIN UTILITY PUMP

POOL-CARE MAIN DRAIN UTILITY PUMP is a powerful and durable utility pump that is designed primarily for draining in-ground swimming pools. The slotted "basket" base measures less than 5 1/2-inches in diameter, which allows the pump to fit inside any standard 8" main drain and seat itself several inches below the top surface of the pool's main drain flange. With a maximum flow rate of 5373 GPH, it can quickly and efficiently remove water from any in-ground Swimming Pool.

MAIN DRAIN PUMP FEATURES:

- Maximum Flow Rate: 5373 GPH or 90 GPM
- Maximum Head Height: 32-feet
- Pumps Down to 1 1/2" to 2" water depth
 (1 1/2" with feet removed from base)
- Fits in standard 8" Pool Main Drain Allowing for Complete Drainage
- Includes 1 1/2" Threaded Barbed Fitting
- Removable Elbow for Vertical or Horizontal Discharge Options
- Integrated Carry Handle
- 25' Cord with Flexible Strain Relief
- Completely Submersible
- Slotted Base Constructed from High Impact Polypropylene
- 316 Marine Grade Stainless Steel Hardware
- Optional Tethered Float Switch for Automatic Shut-Off
- Packed 2 per Master Carton
- 1 Year Limited Warranty*



Main Drain Pump Shown with Optional
Tethered Float Switch for Automatic Shut-Off

TETHERED FLOAT SWITCH FEATURES:

- Mechanically-Activated Snap Action Contacts
- Corrosion Resistant High Impact Polypropylene Float Housing





MAIN DRAIN PUMP - ITEM# 20370

Max. Flow Rate	5373 GPH
Max. Pumping Height	32'
Max. Watts/Amps	593/4.9
Weight	12 lbs.
Dimensions w/ Elbow (W x H)	9 3/4" x 15 1/2"
Dimensions w/out Elbow (W x H)	7 1/4" x 15 1/2"

TETHERED FLOAT SWITCH - ITEM# 20375

Cord Length: 30' with Piggy Back Plug



