

PRODUCT DATA



MasterFormat: 07 19 00

No. 795-A

NOVEMBER 2016
(Supersedes February 2010)

DECK-O-SHIELD™ PLUS

Natural Stone and Salt Water Resistant Sealer

DESCRIPTION

DECK-O-SHIELD PLUS is a premium-grade, ready-to-use, water-based sealer formulated for use on natural stone. DECK-O-SHIELD PLUS is formulated specifically to seal porous surfaces and is ideal to use on pool copings and decks protecting them from salt penetration. It can be used on all porous surfaces such as natural stone, concrete, pavers, and grout. DECK-O-SHIELD PLUS provides a solution to spalling and pitting of porous stone and concrete surfaces caused by salt penetration as well as surface damage caused by freeze-thaw cycles.

USES

DECK-O-SHIELD PLUS repels water and protects virtually all porous surfaces, including decks, porches, patios, and walkways around pools. This includes the following surfaces: natural stone, mortar joint, concrete, brick, concrete block, stucco.

Another advantage DECK-O-SHIELD PLUS provides is that the product will not alter the color or tint of the surface after application. There is no need for worry when applying DECK-O-SHIELD PLUS, because the product should have no adverse effects on surface appearance after application.

FEATURES/BENEFITS

- DECK-O-SHIELD PLUS is not a film-forming material - it penetrates the surface to form an integral barrier to moisture penetration.
- Transparent, non-staining.
- High solids content; one-coat application on most surfaces.
- Surface appearance after application and complete drying is virtually unchanged.
- Reduces entrapment of dirt particles and other contaminants that cause discoloration; inhibits soiling.
- Helps protect against efflorescence and rust staining.
- Provides spill and wipe protection from stains.
- Protects against salt staining and "whitening" caused by salt in the water.
- Water-based, VOC compliant.
- One component.

PACKAGING

1 Gallon (3.79 Liter) Units
5 Gallon (18.93 Liter) Pails

COVERAGE

300 - 475 ft.²/gal. (7.36 - 11.66 m²/L). Coverage rate will vary due to the porosity of the substrate.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F (4° - 32° C), optimum performance and best use is obtained within one year of date of manufacture.

SPECIFICATIONS

- Complies with U.S. EPA, LADCO, and OTC VOC regulations.
- Treated surface is USDA accepted.

TECHNICAL DATA

Dry to Touch: 1 - 2 hours (Typical)
Color: Milky White Emulsion

deck-o-seal®

A DIVISION OF W. R. MEADOWS®

www.deckoseal.com

P.O. BOX 397 • HAMPSHIRE, IL 60140 • PHONE: 800-542-POOL (7665) • FAX: 847-214-2268