

No Power?...No Problem.

Sustainable Solar Powered Irrigation Controllers



Use the power of LEIT

Light Energized Irrigation Technology

Ideal for:



sport/activity fields



medians



pocket parks



retrofits

Features

- Runs on ambient light (solar power)
- 2-28 stations
- No batteries or direct sunlight needed

- Remote control options
- Flexible programming
- Smart control options (LEIT-2ET)

Cities currently using LEIT:

Tucson
Goodyear
Los Angeles
Orlando
Littleton

San Francisco
San Diego
Dallas
Bend
and many more....



DIG Corporation

1210 Activity Drive
Vista, California 92081
www.digcorp.com

800.322.9146
760.727.0914
fax 760.727.0282



LEIT® Irrigation Control Systems

Controllers

Select a controller below then choose the number of solenoids or valve combinations based upon station requirements. Be sure to include a



LEIT 4000
4-8 stations



LEIT X & XRC
4-28 stations

How to specify	
LEIT 400*	* = Station 4, 6, 8 example: LEIT 4004 = 4 station

How to specify	
LEIT X**	** = Station 10, 12, 16, 20, 24, 28 example: LEIT X12 = 12 station

How to specify	
LEIT XRC** (Remote capable)	** = Station 04, 06, 08, 10, 12, 16, 20, 24, 28 example: LEIT XRC28 = 28 station
LEIT Link remote handset (optional)	
LEIT Multi-Pro	Up to 99 controllers
LEIT Master	99 controllers with 99 groups

LEIT XRC | Range 800' line of sight

System components

Choose either the complete valve and solenoid combination or choose the solenoid only then select the appropriate adapter from the list at the bottom of the page.




160HE valves



[or]
LEMA 1600HE solenoid



LEIT key



column mount

How to specify

Solenoid & inline valve

160HE-075	LEMA 1600HE on 3/4" inline valve
160HE-100	LEMA 1600HE on 1" inline valve
160HE-150	LEMA 1600HE on 1 1/2" inline valve
160HE-200	LEMA 1600HE on 2" inline valve

How to specify

Solenoid & anti-siphon valve

160HE-ASV-075	1600HE solenoid with 3/4" ASV
160HE-ASV-075	1600HE solenoid with 1" ASV

How to specify

Solenoid with internal bleed and manual override

LEMA 1600HE	Solenoid with internal bleed and manual override
-------------	--

How to specify

Programming tool to enter controller

LEIT KEY	Programming tool to enter controller
----------	--------------------------------------

How to specify

32" (81 cm) mounting column

MCOL-4000	32" (81 cm) mounting column
MCOL-4000L	48" (122 cm) mounting column

How to specify

35" (89 cm) mounting column

MCOLXS	35" (89 cm) mounting column
MCOLXL	51" (130 cm) mounting column

How to specify

51" (130 cm) mounting column

MKIT 4000	LEIT 4000 column mounting kit
MKIT X	LEIT X & XRC column mounting kit

LEIT-2ET Wireless Irrigation Control System

Controllers

Select the number of controllers, handsets and weather stations (optional) below then choose the number of solenoids or valve combinations based upon station requirements. Be sure to include the mounting option from the system components.

NOTE: One handset can be used for up to 99 controllers or 198 valves.



LEIT-2ET
2 station smart, wireless

How to specify	
LEIT-2ET	Wireless smart controller

Range 350' line of sight

How to specify	
LEIT WWS	Wireless weather station

Range 350' line of sight

Weather station sensors included:	
• Thermometer	• Tipping rain gauge
• Hygrometer	• Solar radiation meter
• Anemometer (WWS only)	

System components

Choose either the complete valve and solenoid combination or choose the solenoid only then select the appropriate adapter from the list at the bottom of the page.



305DC valves



S-305DC solenoid



How to specify

Solenoids & inline valve

305DC-075	S-305DC on 3/4" inline valve
305DC-100	S-305DC on 1" inline valve
305DC-150	S-305DC on 1 1/2" inline valve
305DC-200	S-305DC on 2" inline valve

How to specify

Solenoids & anti-siphon valve

305DC-ASV-075	S-305DC solenoid with 3/4" ASV
305DC-ASV-100	S-305DC solenoid with 1" ASV

How to specify

9-volt DC solenoid

S-305DC	9-volt DC solenoid
---------	--------------------

How to specify

Valve box dome attachment • green

30-830	Valve box dome attachment • green
30-831	Column attachment

How to specify

Valve clip attachment

30-832	Valve clip attachment
30-835	Valve box dome attachment • tan

How to specify

Valve box dome attachment • purple

30-836	Valve box dome attachment • purple
MCOL2S	25" (63 cm) mounting column

How to specify

50" (128 cm) mounting column

Retrofit Existing Valves Using These Solenoid Adapters (For both LEMA 160HE & S-305DC Solenoids)



30-920



30-921



30-922



30-923



30-924



30-925



30-926

Adapts to:

BERMAD series 200,
HIT series 500, DOROT series 80,
GRISWOLD series 2000, DW and
BUCKNER series VB valves

RAIN BIRD DV, DVF, PGA,
PGB (1" only), GB, EFB-CP,
BPE, PESB (1" only)
and ASVF valves

HUNTER series ASV,
HPV, ICV, PGV, SRV,
IBV and ASVF valves

WEATHERMATIC series 12000, 21000,
8200CR valves

IRRITROL series 100, 200B,
205, 217B, 700, 2400, 2500,
2600 and TORO series 220,
P220 valves

SUPERIOR series 950,
HUNTER HBV and TORO
series 252 valves
(1.5" and larger)

RAIN BIRD series
PEB and PESB
(1 1/2" and
2" only) valves