

HAYWARD® NORTHSTAR Replacement™ C-Flange Switchless Design, 6.5" Frame Diameter, Threaded Shaft; Category "N"



FEATURES:

- Two Compartment
- Triple Bearing Protection
- Thermally Protected
- 1081 Design
- Shaft Threads - 7/16-20 UNF-2A
- Class B Insulated
- Open Dripproof
- Continuous Duty
- 65°C Ambient
- 6.5" Diameter Frame
- 303 Stainless Steel Shaft
- Sealed Ball Bearings
- Voltage Selection Device (Dual Voltage Only)
- **Discount Symbol: DS-FPS**

extreme E Premium Energy Efficient, Full Service Factor, Full Rated

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4	1.85	3450	208-230/115	60	6.0-5.5/11.0	ESN1072	\$357	56J	11.02	27
1	1.85	3450	208-230/115	60	8.5-7.8/15.6	ESN1102	\$396	56J	11.27	30
1 1/2	1.60	3450	208-230/115	60	11.0-10.2/20.4	ESN1152	\$454	56J	11.77	33
2	1.35	3450	208-230	60	13.0-11.8	ESN1202	\$531	56J	11.77	35
3	1.60	3450	208-230	60	20.6-19.0	ESN1302	\$796	56J	14.02	47

extreme E Premium Energy Efficient, Low Service Factor, Up/Max Rated

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
1	1.40	3450	208-230/115	60	6.0-5.5/11.0	EUSN1102	\$357	56J	11.02	27
1 1/2	1.25	3450	208-230/115	60	8.5-7.8/15.6	EUSN1152	\$396	56J	11.27	30
2	1.20	3450	208-230/115	60	11.0-10.2/20.4	EUSN1202	\$454	56J	11.77	33
2 1/2	1.10	3450	208-230	60	13.0-11.8	EUSN1252	\$531	56J	11.77	35
3	1.20	3450	208-230	60	16.0-14.8	EUSN1302	\$763	56J	12.52	41

Catalog numbers are for competitive comparison purposes only.

extreme E EXTREME E® represents our most efficient running, highest performing lines of motors.

† All marks shown within this document are properties of their respective owners.

