



CS-271T CHAIN SAW

CS-271T



- Incredible Torque and Throttle Response
- 26.9 cc Commercial-Grade 2-Stroke Engine
- Easy-Access Rear-Mounted Air Filter
- i-30™ Technology Reduces Starting Effort by 30%
- G-Force Engine Air Pre-Cleaner™
- Digital Ignition System
- Anti-Vibration System
- Side Access Chain Tensioner
- Clutch-Driven Automatic/Adjustable Oiler
- Purge Bulb



5 year consumer, 1 year commercial,
and 90 day rental warranty.
Visit www.echo-usa.com/5year to learn more.

The new ECHO CS-271T Chain Saw features a 26.9 cc commercial-grade 2-stroke engine that delivers power and durability. It also features an easy-access, rear-mounted air filter that provides superior filtration for long engine life, an i-30™ starting system which reduces starting effort by 30%, a G-Force Engine Air Pre-Cleaner™ that pulls dust and chips from the air box providing a clean air supply to the engine, a digital ignition system that automatically adjusts engine timing for optimum performance, an anti-vibration system for reduced operator fatigue, and a side access chain tensioner for easy chain adjustment.

5 year consumer, 1 year commercial, and 90 day rental warranty

CS-271T



Model	Engine Displacement (cc)	Engine Displacement (cu in)	Starting System	Ignition System	Purge Bulb	Oiling System	Vibration Reduction System	Available Bar Lengths (in)	Fuel Capacity (fl oz)	Oil Capacity (fl oz)	Dry Weight* (lb.)
CS-271T	26.9	1.64	i-30™	Digital	Yes	Automatic/Adjustable	Standard	12	8.1	5.4	6.6
CS-310	30.5	1.86	i-30™	Digital	Yes	Automatic **	Standard	14	8.5	8.8	8.8
CS-330T	32.6	1.99	Standard	Digital	No	Automatic/Adjustable	Standard	12, 14, 16	10.5	9.8	8.1
CS-341	33.4	2.04	Standard	SAIS	Yes	Automatic/Adjustable	Standard	12, 14, 16	8.5	5.0	7.6
CS-352	34.0	2.08	i-30™	Digital	Yes	Automatic **	Standard	14, 16	8.5	8.8	8.8
CS-360T	36.3	2.21	Standard	Digital	No	Automatic/Adjustable	Standard	12, 14, 16	10.5	9.8	8.1
CS-370	36.3	2.21	i-30™	Digital	Yes	Automatic/Adjustable	Standard	14, 16, 18	13.9	9.5	10.0
CS-400	40.2	2.45	i-30™	Digital	Yes	Automatic/Adjustable	Standard	16, 18	13.9	9.5	10.1
CS-450/450P	45.0	2.75	Standard	Digital	No	Automatic/Adjustable**	Standard	16, 18, 20	15.2	9.5	11.2
CS-500P	50.2	3.06	i-30™	CDI	No	Automatic/Adjustable**	Standard	16, 18, 20	16.9	9.5	10.6
CS-550P	54.1	3.30	Standard	Digital	No	Automatic/Adjustable**	Standard	16, 18, 20	17.9	10.1	13.3
CS-600P	59.8	3.65	Standard	Digital	No	Automatic/Adjustable**	Standard	20, 24, 27	19.1	10.1	13
CS-680	66.8	4.07	Standard	SAIS	No	Automatic/Adjustable***	Standard	20, 24, 27	22.5	13.0	14.5
CS-8000	80.7	4.92	Standard	SAIS	No	Automatic/Adjustable***	Standard	24, 27, 32, 36	28.9	14.1	16.5

* without bar and chain
 ** clutch-driven
 *** with manual override