


Split Bolt Connector – ESB8



- Unplated high-strength silicon bronze accommodates copper to copper connections
- Tin plated, high-strength copper alloy split bolt with spacer separates dissimilar conductors and accommodates copper-to-copper, copper-to-aluminum and aluminum-to-aluminum connections



Part Number	ESB8
Material	Silicon Bronze
Tin Plating	No
Conductor Size	#16 Stranded - #8 Stranded 1.5 mm ² Stranded - 6 mm ² Stranded
Torque (TQ)	165 in lb
Certifications	cULus
Standard Packaging Quantity	100 pc
UPC	78285630492
EAN-13	8711893093971

Oxide inhibitor recommended when used on aluminum conductor.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.