

COMMERCIAL 21
X-SERIES

**PRODUCTIVITY.
COMMERCIAL DURABILITY.
EASE OF USE.**



Known for getting the job done faster, and better, Exmark's commercial-grade 21-inch walk-behind mowers deliver an unmatched quality of cut—and years of worry-free service—that have become the industry benchmarks. Recent design features like the patented front-height adjustment system and single point rear height adjust provide even more versatility when mowing.

FEATURES:

- Equipped with Kawasaki® or Honda® engines.
- 5-inch deep cutting deck provides Exmark® signature cut and superior performance whether bagging or mulching.
- Easy on/off bag design eliminates the need for levers and doors.
- Ground speeds up to 4.2 mph.
- Self-propelled with choice of zone start or Blade Brake Clutch (BBC).



INFINITE SPEED CONTROL

A commercial-proven, multi-cone transmission provides infinite speed control from zero to 4.2 miles per hour. With no gears to change, the Commercial 21 is easy to operate and control.



THE EXMARK SIGNATURE CUT

The true test of a mower is the cut quality it delivers. The Commercial 21 is engineered to consistently deliver an unmatched quality of cut, whether mulching or bagging. A variety of optional blades let you further optimize performance for your specific cutting conditions.



PATENTED FRONT HEIGHT ADJUST

Simple, innovative and built to last, the patented front-height adjustment eliminates the need for pivot-style adjusters.

The mowers landscape professionals trust 2 to 1.*

exmark.com

*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



COMMERCIAL 21

X-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECX180CKA21000	FJ180V Kawasaki KAI	21"	Self-Propelled Zone	123 lbs.	22" x 38.0"¹ x 62.0"
ECX160CHN21000	GXV160 Honda	21"	Self-Propelled Zone	123 lbs.	22" x 38.0"¹ x 62.0"
ECX180CKA210BC	FJ180V Kawasaki KAI	21"	Self-Propelled BBC	130 lbs.	22" x 38.0"¹ x 62.0"

¹ Varies with 0.5" cutting selections.



POWER COMPONENTS

Engine – FJ180V Kawasaki KAI engine governed to 3,300 rpm; GXV160 Honda engine governed to 3,300 rpm.

Air Filter – Dual element air cleaner.

Drive System – Self-propelled, rear-wheel gear-driven.

Transmission – Infinitely variable speed selection, dual wheel drive.

Fuel Capacity – 1 gallon (3.8-L) fuel tank.

Speed – 0.0 mph to 4.2 mph (6.6 kmph) forward.

Speed Control - Finger-tip control.

DECK

Style – Fixed-deck, rear-discharge bagger and mulch plug standard.

Widths Available – 21" (53.3 cm).

Cutting Height – 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Blade – 1 blade at 20.5".

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 5-inch-deep, 1/4-inch-thick die-cast aluminum.

Drive Tires – 9 x 2.5, semi-pneumatic.

Safety Package – Zone start/Blade Brake Clutch (BBC).

Bag Capacity – 2.5 bushels (20 gallons).

ACCESSORIES & OPTIONS

No accessories available.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.