



FORWARD VIBRATORY PLATE COMPACTOR



- 1 **Handle with padded grip** provides the operator with an added level of comfort and vibration isolation
- 2 **Attached swingaway wheel kit**, the ultimate in convenience for jobsite transportation
- 3 **External drain for the engine oil** simplifies servicing by allowing a clean and easy way to drain engine oil
- 4 **Lifting handles** for easy loading and unloading
- 5 **Wraparound steel engine protection with integral lifting bale**, gives the engine the protection it needs and offers a secure lifting point for transportation
- 6 **Large capacity water tank** to use with asphalt compaction applications
- 7 **Heavy duty cast steel base plate** for a smooth quality finish and long life
- 8 **Throttle assembly** is a heavy-duty rack and pinion design made out of cast aluminum



MODEL	EFPC60W	EFPC70W	EFPC90C
DIMENSIONS (LxWxH) - in (mm)	38.2 x 14.2 x 41.3 (970 x 360 x 1,050)	38.2 x 16.5 x 41.3 (970 x 420 x 1,050)	43.3 x 17.7 x 41.3 (1,100 x 450 x 1,050)
OPERATING WEIGHT - lbs (kg)	148 (67)	163 (74)	209 (95)
PLATE SIZE (LxW) - in (mm)	20 x 14.2 (510 x 360)	20.4 x 16.5 (510 x 420)	23.1 x 18.9 (590 x 480)
WORKING SPEED mph (km/h)	0.75 - 0.93 (1.2 - 1.5)	0.75 - 0.93 (1.2 - 1.5)	0.75 - 0.93 (1.2 - 1.5)
VIBRATION FREQUENCY v.p.m. (Hz)	5,640 (94)	5,820 (97)	5,820 (97)
CENTRIFUGAL FORCE lbs (kg)	1,978 (897)	2,630 (1,193)	3,439 (1,560)
COMPACTED AREA ft²/h (m²/h)	5,920 - 6,459 (550 - 600)	6,243 - 6,997 (580 - 650)	6,674 - 7,535 (620 - 700)
MAX. GRADEABILITY - °	20	20	20
ENGINE	HONDA GX160	HONDA GX160	HONDA GX160
ENGINE TYPE	4-STROKE GASOLINE	4-STROKE GASOLINE	4-STROKE GASOLINE
MAX. POWER OUTPUT - kW (hp)	3.6 (4.8)	3.6 (4.8)	3.6 (4.8)