

UNDER WATER WHITE POOL TILE GROUT & SET OR ABOVE WATER GROUT FAST SET REPAIRS

Before mixing and applying the repair material, make sure it is the right color and material match! It is sometimes hard to see exactly what the color will be from computer monitor screens.

Take a small amount of dry material out of the repair kit and mix with water to be the consistency of "Putty". Then, wet the existing surface that you are trying to match and compare the wet sample to the wet existing surface. If the material needs to be darker, add a very small amount of E-Z Patch Black Cement Dye and dry mix well. If the material needs to be lighter, add a very small amount of E-Z Patch Black Cement and dry mix well. If the material needs to be lighter, add a very small amount of E-Z Patch Black Cement Dye and dry mix well. Both colors are available on our website. You can also use any good cement dye. Repeat this process until the color match is satisfactory.

E-Z INSTRUCTIONS:

- **1.** Only dry clay tiles must be soaked first in water for 10 15 minutes.
- 2. Remove all loose material or grout
- 3. Add water to E-Z PATCH® 4 F.S. DRY CEMENT MIX (enough to be used within 5 10 minutes. Mix until you get the consistency of "mashed potatoes:
- 4. <u>SETTING & GROUTING TILE UNDERWATER</u>: Place the wet mix of E-Z PATCH® 4 F.S. into a baggie. Underwater, apply to back of tile and firmly set in place. Completely fill area to be grouted. Using a sponge, wipe off excess grout leaving grout joint
- 5. <u>GROUTING ABOVE WATER</u>: Completely fill area to be grouted. Using a sponge, lightly wipe off excel grout leaving joint full and flush. When dry, remove any excess grout residue "haze" off of the tile

Allow 4 hours set time before swimming

To make a Custom Color with any of our cement type repair supplies, use any cement dye.

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- Fast Set formulas do not require Liquid Bonder
- Product will cure faster in hotter weather, slower in cooler weather
- Product is best stored between 30 degrees F and 110 degrees F

WARNING: CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN