MATERIAL SAFETY DATA SHEET

SECTION I

IDENTITY: E-Z PATCH® # 4 F.S. Pool Tile Cement Dry Mix

SECTION II - Hazardous Ingredients/Identity Information Hazardous Components: Portland Cement (CAS 65997-15-1) OSHA PEL: 50 Mppcf ACGIH TLV: 10mg/m³ - TWA Hazardous Components: Limestone (CAS 474-34-1) OSHA PEL: 5mg/m³ - (respirable): 15mg/m³ (total dust) ACGIH TLV: 10mg/m³ - TWA Hazardous Components: Aluminum Oxide (CAS 1344-28-1) OSHA PEL: 10, 5mg/m³ respirable dust ACGIH TLV: 10 mg/m³

SECTION III - Physical/Chemical Characteristic	S	
Boiling Point: NA	Specific Gravity:	3.1
Vapor Pressure: NA	Melting Point:	ND
Vapor Density: NA	Evaporation Rate:	NA
Solubility in water: < 1%		
Appearance & Odor: White-No Odor		

SECTION IV - Fire and Explosion Hazard Data Flash Point: NA Extinguishing Media: NA Special Fire Fighting Procedures: NA Unusual Fire and Explosion Hazards: NA

SECTION V - Emergency Overview

May cause irritation to eyes, skin and upper respiratory tract. No unusual fire or spill hazard. Off-white powder. Potential Health Effects: EYES: May cause irritation, especially when wet. SKIN: May irritate skin. INHALATION: May cause upper respiratory irritation.

SECTION VI - First Aid Measures

EYES: Flush eyes with plenty of water for at least 15 minutes. If irritation persists, consult a physician.
SKIN: Wash with soap and warm water. If irritation develops, consult a physician
INHALATION: Remove victim to fresh air. If not breathing, give artificial respiration. Get immediate medical attention

NA=Not Applicable

ND=Not Determined

(revised, 01/26/11)

Disclaimer: E-Z Products believes the information contained herein is accurate. However, E-Z Products makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. E-Z Products assumes no responsibility for injury from the use of the product described herein.