



FIRE ROCK

PAVER INFORMATION MANUAL

FIREROCK PRODUCTS, LLC • 888.876.1025 • FIREROCK.US



FIREROCK CONCRETE PAVERS



STRONGER

NEARLY 2X STRONGER THAN THE ASTM C1731 REQUIREMENT





EXCEEDS ASTM 1731 SLIP-TEST STANDARDS



COOLER

HIGHER SOLAR REFLECTANCE THAN THE COMPETITION









FIREROCK PAVERS

FireRock concrete pavers are a handcrafted alternative to natural stone tile that can be used indoors or out. Our unique finishing process adds depth and texture to create the look of natural stone with the ability to choose from a variety of sizes, colors and thicknesses and laid down in almost any configuration you choose. In addition to being a more affordable option than most natural stone, FireRock pavers outperform the competition in independent tests of strength, durability, safety and heat absorption.

















STANDARD SIZES

*ALL SIZES ARE NOMINAL AND INLCLUDE A ½" GROUT LINE (I.E., A 12" X 12" PAVER IS ACTUALLY 11.5" X 11.5")



COPING & TREADS



CUSTOM ORDERS

FireRock is happy to fulfill custom orders. An order is considered custom when it is outside the standard sizes, colors, and coping/ tread options listed in this information guide. There is a surcharge for all custom orders. Call 888.876.1025 or see your FireRock dealer for more details and pricing information and lead times.

7 PIECE RANDOM PATTERN

RECOMMENDED FOR 1" OR 134" PAVERS WITH A 1/2" GROUT LINE



CONTINUOUS LINES



PALLET DETAILS

1"

STANDARD PACKAGING

Includes all 7 sizes on pallet (random pattern)

COVERAGE

270 ft² per pallet, stacked vertically

PALLET WEIGHT

Approx. 3,200 lbs

OF PALLETS PER TRUCK LOAD

14 (approx. 44,800 lbs total)

134"

STANDARD PACKAGING

Includes all 7 sizes on pallet (random pattern)

COVERAGE 198 ft² per pallet, stacked vertically

> PALLET WEIGHT Approx. 3,600 lbs

OF PALLETS PER TRUCK LOAD

14 (approx. 43,200 lbs total)

DRIVEWAY PATTERN

RECOMMENDED FOR 2¾" PAVERS WITH A ½" POLY SAND JOINT

DRIVEWAY PATTERN 6" x 9" 6" x 9 6" x 6' 12" x 12 6" x 6" 6" x 9" 6" x 9" 6" x 9" 6" × 6"

PALLET DETAILS

2³/₄"

STANDARD PACKAGING 1 size per pallet

COVERAGE 105 -112 ft² per pallet, stacked horizotally

PALLET WEIGHT

Approx. 2,940 - 3,136 lbs

OF PALLETS PER TRUCK LOAD

14 (approx.41,160 - 44,100 lbs total)

6" X 6" X 2³/₄"

TOTAL UNITS 448 units, stacked horizontally

> COVERAGE 112 ft² per pallet

PALLET WEIGHT Approx. 3,136 lbs

6" X 9" X 2³/₄"

TOTAL UNITS 280 units, stacked horizontally

> COVERAGE 105 ft² per pallet

PALLET WEIGHT Approx. 2,940 lbs

12" X 12" X 2¾"

TOTAL UNITS 112 units, stacked horizontally

> COVERAGE 112 ft² per pallet

PALLET WEIGHT Approx. 3,136 lbs

NON-PITTED PAVERS

FireRock non-pitted pavers offer an alternative to our classic pitted pavers while still maintaining the durability and affordability FireRock pavers are known for.

Our non-pitted pavers are hand-crafted using the same proprietary concrete mixture used for our pitted pavers. However, with these pavers, we eliminate our unique finishing process, which results in a smoother appearance.

Though our non-pitted pavers won't have the pitting that characterizes our standard pavers, they may still have small air bubbles, which are most prominent around the outside perimeter. These air bubbles are a by-product of the hand-crafted process used to create each paver.









FIREROCK PRODUCTS, LLC 888.876.1025 | FIREROCK.US 1500 1ST AVE N, BIRMINGHAM, AL 35203