

# KOSHIN 2", 1/2 HP SUBMERSIBLE PUMP





## **Specifications**

| Model           | PX-65011 |
|-----------------|----------|
| Discharge Size  | 2"       |
| Motor Output    | 1/2 HP   |
| Delivery Volume | 68.5 GPM |
| Total Head      | 32.8 Ft. |
| Voltage         | 110 V    |
| Rated Current   | 6.5 Amps |
| Cable Length    | 19.7 Ft. |
| Net Weight      | 24 Lbs.  |

# PX-65011


#### **Features**

- Unique design permits either vertical or horizontal discharge.
- Impeller and casing are manufactured from a blended rubber compound providing maximum wear resistance, up to three times over cast iron.
- Water is channeled through the outer wall to cool the motor for maximum endurance.
- It is compact, light-weight, easy to carry and handle.
- Due to double mechanical seal employed for the shaft, and the SIC at bottom, the shaft hardly wears out and can be used over a long period of time.
- Liquid paraffin is used in the shaft seal, therefore water will not be contaminated even in the case of oil leakage.
- The cord is of uni-body construction ensuring excellent water tightness.
- The built-in thermal protector turns off the power supply in case of overload operation thus protecting the motor.

## **Applications**

- Construction site, excavations, well casings and general dewatering.
- · Utilities, manhole and vault draining.
- Residential, draining of basements, crawl spaces and swimming pools.

### **Performance**





Distributed by:

## **KOSHIN AMERICA CORP.**