



667 Threaded

668 Solder

DIMENSIONS (INCHES)				Approx. Weight	Approx. Weight	C <sub>v</sub>
SIZE	A	B	C	667	668	
1/4	1.63	2.84	2.13	-	0.60	5.6
3/8	1.63	2.84	2.13	1.63	0.60	10.7
1/2	1.69	2.91	2.13	1.78	0.63	17.6
3/4	1.84	3.31	2.13	2.31	0.88	32
1	2.19	3.94	2.41	2.84	1.25	54
1 1/4	2.42	4.34	2.94	3.00	1.75	97
1 1/2	2.44	4.94	2.94	3.22	2.12	135
2	2.84	6.03	3.19	3.97	3.20	230
2 1/2	3.50	7.44	3.94	4.66	6.25	337
3	3.97	8.63	5.13	5.28	9.62	536
4	4.56	10.00	6.78	-	15.50	960

### RATING

- 200 PSI NON-SHOCK

### FEATURES

- FORGED BRASS BODY
- THREADED OR SOLDER ENDS
- THREADED BONNET
- INTEGRAL SEAT
- ADJUSTABLE PACKING NUT
- NON-RISING STEM
- FORGED SOLID WEDGE DISC
- IRON HANDWHEEL
- 100% FACTORY TESTED
- INTERNATIONAL

MATERIAL SPECIFICATION			
1	Handwheel Nut	Brass	ASTM B16
2	Nameplate	Aluminum Sheet	Commercial
3	Handwheel	Cast Iron	ASTM A48, Class 35
4	Stem	Brass	ASTM B124, C37700
5	Packing Nut	Forged Brass	ASTM B283, C37700
6	Gland	Brass Rod	ASTM B124, C37700
7	Packing Ring	Non-Asbestos Synthetic Fibers	
8	Bonnet	Forged Brass	ASTM B283, C37700
9	Locknut	Brass Rod	ASTM B16, C36000
10	Wedge	Forged Brass	ASTM B283, C37700
11	Body	Forged Brass	ASTM B283, C37700

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to [www.hammondvalve.com](http://www.hammondvalve.com). Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).