

CS6000B WaterPro Serial Series available with “plus OZONE”




STANDARD FEATURES

M7® Technology Equipped
 1.375/5.5KW or 1.0/4.0KW, Fixed 15" Heater Assembly
 EZ Access Foot Heater
 Spaside Control
 12V Light Assembly
 All Circuits Convertible to 120 or 240VAC
 Heater "ON" Indicator Light
 Standard, Economy & Sleep Modes
 Amp Receptacles
 Freeze Protection
 Easy To Install & Service
 Installation Kit (see below)
 Detailed Owner's Manual & Wiring Diagram
 US and Canada UL Recognized

OPTIONS

"Plus Ozone" Built-In
 Various Heater Wattages



Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Htr Wattage	Spaside Included
CS6220B-UZ-WP	VS511SZ	2 SPD	2 SPD	N/A	YES	5.5kW	 VL701S Series 7.4"L x 3.2"H
CS6230B-UZ-WP	VS510SZ	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW	
CS6330B-UZ-WP	VS520SZ	2 SPD	2 SPD	1 SPD (12A)	YES	5.5kW	

Also Available in: Plus Ozone Option (-03 Suffix), Titanium Element (-T Suffix) & 4.0kW Heater Assy (-4.0 suffix)
 Refer to price list for the complete list of model numbers.

SPASIDE OPTIONS



Auxiliary Spaside
HQ PT#: 34-51574-K
 7.5"L x 2.3"H

For a complete list of parts, refer to our Replacement Parts Section in the back of this catalog

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (see above)
 Spaside Labels
 Spaside Adapter Plate
 8.5"L x 4"H
 48" Component Cords
 2" Tailpieces w/Gaskets
 12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact Hydro-Quip for more details.

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ
ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S)	MAXIMUM AMPS
PUMP(S)	12A
BLOWER	12A
OZONE	1A
CIRCULATION PUMP	4A
LIGHT	1A
HEATER	23A (5.5KW) OR 18A (4.0KW)

REQUIRED FLOW RATE:

SYSTEM DIMENSIONS:

SHIPPING WEIGHT:

PACKAGING / SHIPPING :

25 GPM
 15"W x 11"H x 6"D
 18 LBS
 INDIVIDUAL (HQ STOCK)
 FOB CORONA, CA 92880