

I-40

Radius: **44' to 76'**
Flow: **7.6 to 33.7 GPM**
Inlet: **1"**

FEATURES

- Models stainless riser: 4", 6"
- Arc setting: 50° to 360°
- Factory installed rubber cover
- Nozzle choices: 12
- Nozzle ranges I-40: #8 to #25
- Nozzle ranges I-40-ON: #15 to #28
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water lubricated gear-drive
- Warranty period: 5 years
- ▶ Opposing nozzle 360 degree model
- ▶ Automatic arc return
- ▶ Non-strippable drive
- ▶ Part- and full-circle in one model
- ▶ Color-coded nozzles
- ▶ Reclaimed water ID
- ▶ Stainless steel riser
- ▶ Drain check valve (up to 15' of elevation)

OPERATING SPECIFICATIONS

- Radius I-40: 44' to 69'
- Radius I-40-ON: 52' to 76'
- Flow I-40: 7.6 to 29.5 GPM
- Flow I-40-ON: 13.0 to 33.7 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approx.
- Nozzle trajectory: 25°

▶ = *Advanced Feature descriptions on page 30*



I-40 Reclaimed

Available as a factory installed option on all models



I-40 High Speed

Available as a factory installed option on all models



I-40-04

Overall height: 7⅞"
Pop-up height: 4"
Exposed diameter: 2"
Inlet size: 1"



I-40-06

Overall height: 10¼"
Pop-up height: 6"
Exposed diameter: 2"
Inlet size: 1"

I-40 – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS = 4" Pop-up I-40-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve and 6 nozzles	(blank) = No option HS = High speed HS-R = High-speed and reclaimed water ID R = Reclaimed water ID	#8 to #25 = Factory installed nozzle number

I-40-ON – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Opposing Nozzle Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS-ON = 4" Pop-up I-40-06-SS-ON = 6" Pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve and 6 nozzles	(blank) = No option ON = Full circle opposing nozzles ON-R = Full-circle opposing nozzles and reclaimed water ID HS = High speed HS-R = High speed and reclaimed water ID R = Reclaimed water ID	#15 to #28 = Factory installed nozzle number

Examples:

I-40-04-SS = 4" Pop-up, adjustable arc, stainless steel riser, with check valve

I-40-04-SS - ON-R - 23 = 4" Pop-up, adjustable arc, stainless steel riser, with check valve, and reclaimed water ID and #23 nozzle

I-40-06-SS - 15 = 6" Pop-up, adjustable arc, stainless steel riser, with check valve and #15 nozzle

I-40 NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr ■ ▲	
8 (40) 	40	44	7.6	0.76	0.87
	50	45	8.4	0.80	0.92
	60	46	9.2	0.84	0.97
10 (41) 	50	49	10.3	0.83	0.95
	60	50	11.3	0.87	1.00
	70	51	12.2	0.90	1.04
13 (42) 	50	50	11.1	0.85	0.99
	60	51	12.3	0.91	1.05
	70	52	13.3	0.95	1.08
15 (43) 	80	53	14.2	0.97	1.12
	50	54	13.8	0.91	1.05
	60	55	15.7	1.00	1.15
23 (44) 	70	57	16.6	0.98	1.14
	80	59	18.3	1.01	1.17
	60	62	21.3	1.07	1.23
25 (45) 	70	64	23.0	1.08	1.25
	80	65	24.5	1.12	1.29
	90	66	25.9	1.14	1.32
25 (45) 	60	66	23.9	1.06	1.22
	70	67	25.8	1.11	1.28
	80	68	27.7	1.15	1.33
25 (45) 	90	69	29.5	1.19	1.38

I-40 HIGH-SPEED NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr ■ ▲	
8 (40) 	40	41	7.6	0.87	1.00
	50	41	8.4	0.96	1.11
	60	42	9.2	1.00	1.16
10 (41) 	50	45	10.3	0.98	1.13
	60	46	11.3	1.03	1.19
	70	47	12.2	1.06	1.23
13 (42) 	80	47	13.0	1.13	1.31
	50	46	11.1	1.01	1.17
	60	47	12.3	1.07	1.24
15 (43) 	70	48	13.3	1.11	1.28
	80	49	14.2	1.14	1.31
15 (43) 	50	51	13.8	1.02	1.18
	60	52	15.7	1.12	1.29
	70	53	16.6	1.14	1.31
23 (44) 	80	54	18.3	1.21	1.40
	60	58	21.3	1.22	1.41
	70	59	23.0	1.27	1.47
23 (44) 	80	60	24.5	1.31	1.51
	90	61	25.9	1.34	1.55
25 (45) 	60	59	23.9	1.32	1.53
	70	61	25.8	1.33	1.54
	80	62	27.7	1.39	1.60
25 (45) 	90	63	29.5	1.43	1.65

I-40 NOZZLES

Standard/High-Speed

**I-40 Opposing Nozzle 360° Model****I-40 DUAL OPPOSING NOZZLE PERFORMANCE DATA**

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr ■ ▲	
15 Gray 	50	52	13.0	0.46	0.53
	60	54	13.2	0.44	0.50
	70	56	14.4	0.44	0.51
	80	57	15.5	0.46	0.53
18 Red 	50	58	13.7	0.39	0.45
	60	59	15.2	0.42	0.49
	70	60	16.6	0.44	0.51
	80	62	17.8	0.45	0.51
20 Dk. Brown 	60	63	19.1	0.46	0.53
	70	64	20.9	0.49	0.57
	80	66	22.3	0.49	0.57
	90	66	23.9	0.53	0.61
23 Dk. Green 	60	65	20.4	0.46	0.54
	70	66	22.3	0.49	0.57
	80	67	24.0	0.51	0.59
	90	68	25.6	0.53	0.62
25 Dk. Blue* 	60	66	22.0	0.49	0.56
	70	68	24.0	0.50	0.58
	80	69	25.9	0.52	0.60
	90	70	27.2	0.53	0.62
28 Black 	70	70	28.9	0.57	0.66
	80	72	30.9	0.57	0.66
	90	74	32.9	0.58	0.67
	100	76	33.7	0.56	0.65

* Factory installed nozzle

Notes:

All precipitation rates calculated for 180° operation.
For the precipitation rate for a 360° sprinkler, divide by 2.
Precipitation rates for the ON-Opposing Nozzle model are calculated at 360 degrees.

I-40 NOZZLES

Opposing

Front



Back

