

PRO-SPRAY®

Models: **Shrub, 2", 3", 4", 6", 12"**
Inlet: **½"**

FEATURES

- Models: Shrub, 2", 3", 4", 6", 12"
- Compatible with all female threaded nozzles
- Side inlet (SI) version available in 6" and 12"
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation)
- Check valve available on 4", 6", 12"
- Reclaimed water ID cap

USER INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 52*



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps

PRO-SPRAY® - SPECIFICATION BUILDER: ORDER 1 + 2

1 Models	2 Options
PROS-00 = Shrub Adapter	(blank) = No option
PROS-02 = 2" Pop-up	CV = Factory-installed drain check valve (Pop-up models only, 6" and 12" models ordered as CV will come as no side inlet)
PROS-03 = 3" Pop-up	CV-R = Factory-installed reclaimed body cap (Shrub molded in purple)
PROS-04 = 4" Pop-up	
PROS-06-SI = 6" Pop-up with side inlet	
PROS-06 = 6" Pop-up (no side inlet)	
PROS-12-SI = 12" Pop-up with side inlet	
PROS-12 = 12" Pop-up (no side inlet)	

Examples:

PROS-04 = 4" pop-up

PROS-06 - CV = 6" pop-up, drain check valve

PROS-12 - CV-R = 12" pop-up, drain check valve, reclaimed body cap



PROS-00

Retracted height: 1½"
Inlet size: ½"



PROS-02

Retracted height: 4"
Pop-up height: 2"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-03

Retracted height: 5"
Pop-up height: 3"
Exposed diameter: 2¼"
Inlet size: ½"
Shut-Off



PROS-04

Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"
Shut-Off



[A] PROS-06-SI

[B] PROS-06

Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



[A] PROS-12-SI

[B] PROS-12

Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"