

# X-CORE®

Number of Stations: **2, 4, 6, 8**  
Type: **Fixed**

## FEATURES

- Number of stations: 2, 4, 6, 8
- Type: Fixed
- Enclosures: Indoor or outdoor plastic
- Independent programs: 3
- Start times per program: 4
- Max. station run time: 4 hrs
- Built-in Solar Sync®
- Programmable rain delay
- Non-volatile memory
- Warranty period: 2 years
- ▶ Easy Retrieve™ memory
- ▶ QuickCheck™
- ▶ Cycle and Soak
- ▶ Solar Sync Delay
- ▶ Automatic short circuit protection
- ▶ Seasonal Adjustment: Global or automatic updates with Solar Sync
- ▶ Delay between stations
- ▶ Sensor programmability

## ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV: (24 VAC): 0.28 A
- Sensor inputs: 1
- Operating temperature: 0° F to 140° F

## APPROVALS

- CE, UL, cUL, C-tick, FCC
- ▶ = *Advanced Feature descriptions on page 88*



**Plastic Indoor**  
Height: 6.5"  
Width: 5.75"  
Depth: 2"



**Plastic Outdoor**  
Height: 8.6"  
Width: 7"  
Depth: 3.75"

CONTROLLERS

### X-CORE – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Transformer	3 Indoor/Outdoor	4 Options
<b>XC-2</b> = 2-station (indoor model only)  <b>XC-4</b> = 4-station  <b>XC-6</b> = 6-station  <b>XC-8</b> = 8-station	<b>00</b> = 120 VAC <b>01</b> = 230 VAC	<b>(blank)</b> = Outdoor model  <b>i</b> = Indoor model	<b>(blank)</b> = No option  <b>E</b> = 230 VAC with European connections  <b>A</b> = 230 VAC with Australian connections (Australian outdoor models have internal transformer with cord)

**Examples:**  
XC-200i = 2-station 120 VAC indoor controller, with plastic cabinet  
XC-400 = 4-station 120 VAC outdoor controller, with plastic cabinet  
XC-600i = 6-station 120 VAC indoor controller, with plastic cabinet  
XC-800 = 8-station 120 VAC outdoor controller, with plastic cabinet