

# PRS40

PRESSURE REGULATED

Models: **Shrub, 4", 6", 12"**  
 Pressure Regulation: **40 PSI**

## FEATURES

- Models: Shrub, 4", 6", 12"
- Gray identification cap for easy field ID
- Innovative directional flush plug design
- 6" and 12" models come standard as no side inlet, ensuring proper installation with check valve
- Drain check valve installed (14' of elevation) comes standard
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve
- ▶ Pressure regulated to 40 PSI
- ▶ FloGuard™ technology

## OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

## FACTORY INSTALLED OPTIONS

- Reclaimed water ID cap
- FloGuard technology available for check valve models

## USER INSTALLED OPTIONS

- Reclaimed water ID cap (P/N 458562)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 52*



### PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



### Related Solutions: MP Rotator

PRS40 is designed specifically for the MP Rotator®



### PROS-00-PRS40

Retracted height: 4½"  
 Inlet size: ½"



### PROS-04-PRS40-CV

Retracted height: 5⅞"  
 Pop-up height: 4"  
 Exposed diameter: 2¼"  
 Inlet size: ½"



### PROS-06-PRS40-CV

Retracted height: 8¾"  
 Pop-up height: 6"  
 Exposed diameter: 2¼"  
 Inlet size: ½"



### PROS-12-PRS40-CV

Retracted height: 16⅞"  
 Pop-up height: 12"  
 Exposed diameter: 2¼"  
 Inlet size: ½"

SPRAYS

## PRS40 – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Specialty Options
<p><b>PROS-00-PRS40</b> = 40 PSI regulated shrub adapter</p> <p><b>PROS-04-PRS40-CV</b> = 40 PSI regulated 4" pop-up with drain check valve</p> <p><b>PROS-06-PRS40-CV</b> = 40 PSI regulated 6" pop-up with drain check valve</p> <p><b>PROS-12-PRS40-CV</b> = 40 PSI regulated 12" pop-up with drain check valve</p>	<p><b>(blank)</b> = No option</p> <p><b>R</b> = Factory-installed reclaimed body cap</p> <p><b>F</b> = FloGuard technology</p> <p><b>F-R</b> = FloGuard technology with reclaimed body cap</p>

### Examples:

- PROS-04-PRS40-CV = 4" Pop-up regulated at 40 PSI, drain check valve
- PROS-06-PRS40-CV-F = 6" Pop-up regulated at 40 PSI, drain check valve, with FloGuard technology
- PROS-12-PRS40-CV-R = 12" Pop-up regulated at 40 PSI, drain check valve, reclaimed body cap